

The EBS1 is a European design that mounts into a cabinet above the cooktop with only a slim sliding drawer visible, fitting seamlessly into today's modern kitchen. The easy to clean design features bright LED lighting, powerful 400 CFM Max blower speed, while remaining quiet at 5 sones at high speed.

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
24 in.	EBS1244SS	S1104811 (qty.: 1) & S1104812 (qty.: 1)	S1104970
30 in.	EBS1304SS	S1104811 (qty.: 1) & S1104812 (qty.: 1)	S1104970
36 in.	EBS1364SS	S1104813 (qty.: 1) & S1104814 (qty.: 1)	S1104970

c (UL) us





SPECIFICATION SHEET

HVI PERFORMANCE									
	Size	Damper	Sones		CFM				
Duct Orientation			Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.
Round - Vertical	6-in.	Included	1.2	3.0	5.0	190	270	350	370 ‡

‡ CFM reduction to 300 is available. Review Installation instructions for more details.

FEATURES	
Max Blower CFM**	400
Control type	3-speed Mechanical push-button
Delay off	Yes
Filter Clean Reminder	Yes
Heat Sentry™	No
ADA Capable	No
Lighting	1-level LED (bulbs included)
Grease Filter	Aluminum (Qty. 2)
ENERGY STAR®	No
Recirculation	Non-ducted filters sold separately
AC INDUT	



120 V, 60 Hz - 3.6 AMPS

OPTIONAL ACCESSORIES				
Non-duct kit	S1104971			
3¼ in. x 10 in. to 6 in. Round Duct Transition	411			

MOUNTING HEIGHT


27 in. to 32 in. from cooktop to bottom of hood

LIMITED WARRANTY


1-year

See installation manual for full warranty text.

FOR INDOOR USE ONLY







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

1104963A

Venmar Ventilation ULC

926 West State Street, Hartford, WI 53027 550 Lemire Blvd., Drummondville Québec Canada J2C 7W9

1 800-558-1711 1 800-567-3855

www.broan-nutone.com www.broan-nutone.ca

Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

^{**} Max. blower CFM indicates the performance of the hood blower in open air.