

KLIPSCH PSM-525-T

FULL-RANGE 5.25" INDOOR/OUTDOOR
PROFESSIONAL SURFACE MOUNT LOUDSPEAKER

Klipsch®



MORE BASS, LESS SPACE WITH THE ALL-NEW TRACTRIX® HYPERFOLD PORT™

Klipsch is all about high efficiency, low distortion. Building upon that legacy, we're introducing the all-new patented Tractrix® Hyperfold Port™ engineered to extend port length for maximum bass power via proprietary five-step folded design. Its increased airflow eliminates chuffing and port noise while providing a greater dispersion pattern for larger coverage areas.

IPX6 RATED FOR COMMERCIAL ENVIRONMENTS

Perfect for indoor and outdoor commercial installations around the globe, the Klipsch PSM-525-T is IPX6 Rated. Your clients will rest easy knowing their new speakers will be water-resistant and rainproof for the most challenging commercial environments.

MULTIPLE TAP SETTINGS

The PSM-525-T includes a multi-tap transformer for 70 or 100 volt installations. There is also a bypass position that allows normal 8 ohm operation for installations that do not require a transformer.

SET SCREWS ON GRILLE

The included set screws on each grille ensures a secure fit between the speaker and grille, while making sure the grilles stay on the enclosures regardless of the environment.

1" TITANIUM COMPRESSION DRIVER FOR EFFORTLESS, HIGH-CLARITY DETAIL

Klipsch outperforms the competition with our all-new 1" Titanium-loaded floating driver bridge with wide dispersion phase plug. Using our patented mumps technology, the PSM-525-T gives any space extra-wide coverage while providing even and consistent energy for your project.

PHOENIX CONNECTOR FOR SIMPLIFIED INSTALLATION

The PSM-525-T employ a phoenix connector for quick and intuitive connection.

SPECIFICATIONS

FREQUENCY RESPONSE ¹	58Hz-20kHz +/- 4dB, 48Hz -10dB
POWER HANDLING ²	65 watts (16.7V) 55Hz-10kHz (260 watts peak)
CALC. MAX. CONT. OUTPUT ³	104dB
SENSITIVITY ⁴	89dB
COVERAGE	100° +/- 20° 1kHz-20kHz
DIRECTIVITY INDEX	7dB +/- 1.5dB 1kHz-20kHz
NOMINAL IMPEDANCE	8 ohms 4.3 ohms at 175Hz minimum
ACOUSTIC CROSSOVER	2kHz
TRANSDUCERS	5.25" woofer 1" titanium compression driver, on a K-1200M horn/tweeter bridge
ENCLOSURE MATERIAL	All Weather ABS Plastic, Paintable
IP RATING	IPX6
ENCLOSURE TUNING	Vented via 3 folded Tractrix ports
INPUT CONNECTORS	4 pin euro block
TRANSFORMER TAPS	70V: 30W, 15W, 7.5W, 3.8W 100V: 30W, 7.5W, 3.8W Bypass position: 8 ohms nominal
DIMENSIONS [WITH BRACKET]	12.13"(309mm) x 9.5"(242mm) x 6.5"(166mm) [8.38"(213mm)]
WEIGHT	7.75 lbs (3.52kg)

¹ 1m, half space, anechoic

² AES standard, continuous pink noise 50hz-10kHz, 6dB peaks

³ Calculated at 1m at power handling power input

⁴ SPL at 1m half space, anechoic with 2.83V pink noise input

