EQUILITY™
SINGLE LEVER AND VESSEL FAUCETS



- Minimalist cast brass spout
- Ceramic disc valve cartridge
- 3/8" compression braided, stainless steel flexible supply hose
- Lead Free—faucet contains ≤0.25% total lead content by weighted volume
- Low flow rate: 1.2 gpm (4.5 L/min)
- Red and Blue (hot/cold) indicator markings on handle

CODES AND STANDARDS

Meets or Exceeds ASME A112.18.1/ CSA B125.1, NSF 61/Section 9

EPA WaterSense® Certified

Certified Compliant with ≤0.25% Weighted Average Lead Content Regulations

CEC and CALGreen® Compliant

AVAILABLE FINISHES	FINISH CODE
Polished Chrome	100
Brushed Nickel	144
Matte Black	243


DESCRIPTION	PRODUCT NUMBER
Single Lever Faucet	D35109100RB.XXX
Vessel Faucet	D35109150RB.XXX

ROUGH-IN DIAGRAM
SHOWN ON NEXT PAGE

CALGreen® is a registered trademark of California Building Standards Commission.

EQUILITY™

SINGLE LEVER AND VESSEL FAUCETS



NOTE: MOUNTING HOLES ARE 1-3/8" D. (35 mm)

IMPORTANT: These measurements are subject to change or cancellation.
No responsibility is assumed for use of superseded or voided pages.

PART OF LIXIL

©2018 AS America Inc.