

SBC695OSTRIPLE



34.25" x 23.88" x 25" (H x W x D)

Outdoor/indoor commercial beer dispenser for built-in or freestanding use, with complete triple tap kit, digital thermostat, and 304 grade stainless steel exterior

Highlights:

Commercially listed to NSF-7 standards

Full-sized capacity can store a full half barrel, two slim quarter barrels, or up to three Cornelius style or sixtels

Versatile service with a triple tap draft tower

Product Features:

| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings | |
|---------------------------|---|--|
| Weatherproof design | Solid construction allows placement in the outdoors | |
| Built-in capable | Front-breathing design allows fully recessed installation under counters | |
| Full-sized beer dispenser | Large interior can accept a full half barrel keg, two slim quarter kegs, or up to three sixth barrel or Cornelius style kegs | |
| Complete tap kit | Includes a 5 lb. CO2 tank and regulator, triple tap draft arm, Sankey American tap, connection hardware, and cleaning kit | |
| Triple tap system | Triple draft tower allows you to serve from three 1/6 (sixtel) sized kegs | |
| Stainless steel exterior | Door and cabinet are wrapped in 304 grade stainless steel for lasting durability in the outdoors | |
| Professional handle | Blade style handle in brushed stainless steel matches many popular styles of cabinetry and grill details | |
| Digital thermostat | Electronic controls ensure easy temperature management for optimum beer storage, with a readout viewable in Celsius or Fahrenheit | |





SBC695OSTRIPLE Specifications:

| Overview | | | |
|-------------------------------|----------------------------------|--|--|
| Height of Cabinet | 34.25" (87 cm) | | |
| Width | 23.88" (61 cm) | | |
| Depth | 25.0" (64 cm) | | |
| Depth with Handle | 26.88" (68 cm) | | |
| Depth with door at 90° | 47.75" (121 cm) | | |
| Capacity | 6.04 cu.ft. (171 L) | | |
| Defrost Type | Automatic | | |
| Door | Stainless Steel | | |
| Cabinet | Stainless Steel | | |
| US Electrical Safety | ETL | | |
| Canadian Electrical Safety | ETL-C | | |
| Sanitation | ETL-S | | |
| Amps | 1.3 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 108.0 lbs. (49 kg) | | |
| Shipping Weight | 113.0 lbs. (51 kg) | | |
| Estimated Time to Ship | 3 to 5 days | | |
| Parts & Labor Warranty | 1 Year | | |
| Compressor Warranty | 5 Years | | |
| Kegerator | | | |
| Door Swing | RHD | | |
| Reversible | Yes | | |
| Tap Kit | Yes | | |
| Height with Tap | 52.13" (132 cm) | | |
| Number of Taps | 3 | | |
| Thermostat Type | Digital | | |
| Interior Light | Yes | | |
| Fan Type | Interior and Exterior | | |
| Refrigerant | R600a | | |
| Refrigerant Amount | 1.76 oz. | | |
| High Side PSI | 220.0 | | |
| Low Side PSI | 43.0 | | |
| Inter Height | 27.0" (69 cm) | | |
| | | | |
| Interior Width | 20.38" (52 cm) | | |
| Interior Width Interior Depth | 20.38" (52 cm) 21.25" (54 cm) | | |
| | | | |

| Compressor Step Depth | 2.5" (6 cm) |
|-----------------------|-----------------|
| Wheel Qty | 4 |
| Surface | Stainless Steel |
| Temperature Range | 32º to 50ºF |



