

Specifications

Speaker Design

2 - way

Woofer Size | in [mm]

3 1/2 [89]

Tweeter Size | in [mm]

1/2 [13]

DC Resistance | ohm

3.2

Peak Power (watts, per ANSI/CTA-2031-A)

90

Recommended Amplifier Power (watts RMS)

30

Sensitivity [SPLo] | dB @ 1W, 1m

88

Effective Frequency Range | Hz

80-20k

Mounting Hole Diameter | in [mm]

3 [78]

Top Mount Depth | in [mm]

1/4 [6]

Bottom Mount Depth | in [mm]

1 11/16 [42]

Tweeter Protrusion | in [mm]

1/8 [3]

Grilles

No

Tweeter Magnet Material

Neodymium

Tweeter Dome Materia

PEI [polyether imide]

Tweeter Design

Balanced dome

Woofer Cone Material

Polypropylene

Woofer Surround Material

Polyester foam

Support



Manuals

2019 CS Coaxials | Multilingual | Download
(/app/manuals/mids_tweets/cs/2019_CS_Coax.pdf)

Do you have a different model? Click Here (/product-manuals)



Support Links

Subwoofer / Speaker FAQ (/faq)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (mailto:support@kicker.com)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (mailto:warranty@kicker.com)