





PUT SOME AWESOME IN YOUR BACKYARD

POWERFUL PERFORMANCE

- Exhaust either vertically or horizontally through a 10-inch round duct
- Two powerful blowers capable of exhausting up to 1,200 CFM
- Four LED lamps brilliantly illuminate the cooking area
- Perfect for any grilling arrangement with top or rear discharge capabilities
- 33" depth (Most grill installs are 6" from non combustible wall)
- Seamless, hand-crafted welded edges ensure strength and durability
- 304 Stainless steel exterior is easy to keep clean and eliminates grease traps
- Commercial-grade, high luster baffle filters are attractive and long-lasting

At XO, we believe that a good design is something everyone can afford

WORLD CLASS SERVICE | COMPREHENSIVE WARRANTIES OUR LASTING COMMITMENT TO YOU



For 90 days, all our products are backed by our unique Love It or Leave It Guarantee*

XOGVENT_

1200 CFM EXAUST HOOD



FEATURES

Stainless Steel

FINISH

- Exhaust either vertically or horizontally through a 10-inch round duct
- Two powerful blowers capable of up to 1,200 CFM
- Four LED lamps brilliantly illuminate cooking area
- 33" depth a must for proper capture (Most grill installs are 6" from non combustible wall)
- Seamless, hand-crafted welded edges ensure strength and durability
- 304 Stainless steel exterior
- Commercial-grade, high luster baffle filters



SPECIFICATIONS

115VAC 60HZ 8.5 AMP ELECTRICAL DIMENSIONS

H 18" W 36", 42", 48"

D 33"

RECOMMENDED MOUNTING HEIGHT

ABOVE COOKING 30" - 42"

OPTIONS

36"Wx6"H Duct Cover 42"Wx6"H Duct Cover 48"Wx6"H Duct Cover 36"Wx12"H Duct Cover 42"Wx12"H Duct Cover 48"Wx12"H Duct Cover XOGV48X12DC Telescoping 28"Wx55"H XOGV18TELDC (2 Sections for ceiling height up to 11.5 ft)

XOGV36X6DC XOGV42X6DC XOGV48X6DC XOGV36X12DC XOGV42X12DC



XO is exclusively distributed by EASTERN MARKETING CORP. 24 Eisenhower Parkway Roseland, NJ 07068

XOGVENT_

CLEARANCE TO COMBUSTIBLE CONSTRUCTION:

- If installed under any combustible construction the area above the cooking surface of the ٠ grill must be covered with an approved exhaust hood.
- It is highly recommended the hood be sized with a 3" overhang on all exposed sides.
- The exhaust hood shall provide no less than 1,200 CFM of proper exhaust ventilation.
- The exhaust hood must be approved for outdoor installation and used with a dedicated ٠ GFCI branch circuit.



xoappliance.com | 800.966.8300



XO is exclusively distributed by 24 Eisenhower Parkway Roseland, NJ 07068