

## DA 6498 W Pure Grey

Wall ventilation hood  
with energy-efficient LED lighting and touch controls for simple operation.



- Lots of headroom – 35 1/2 (899)Inch wide with an exclusive glass design
- Unique user convenience – Con@ctivity
- Energy-efficient and quiet
- Safe and easy to clean - Miele CleanCover

EAN: 4002515961513 / material number: 10811940

<b>Construction type</b>	
Wall ventilation hood	•
<b>Design</b>	
Color	Graphite grey
Edge extraction	•
<b>Operating modes</b>	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF25-900
<b>Control panel</b>	
Electronic controls	•
Touch controls on glass	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Networking of domestic appliances</b>	
WiFiConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters	1
<b>Lighting</b>	
LED ClearView lighting	•
Light intensity in Lx	440
Color temperature in K	3,500
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Air throughput with max. duct diameter in vented mode (not for external version)</b>	
Air throughput	Values upon request
<b>Safety</b>	
Safety shut-off	•
Single-ply safety glass (ESG)	•

DA 6498 W Pure Grey

Wall ventilation hood  
with energy-efficient LED lighting and touch controls for simple operation.



<b>Technical data</b>	
Overall hood height for vented and external in in.(mm)	21 3/4 (550)
Overall hood height for recirculation in in.(mm)	21 3/4 (550)
Canopy width in in.(mm)	35 1/2 (899)
Height of hood canopy in in.(mm)	21 3/4 (550)
Depth of hood canopy in in.(mm)	20 7/8 (530)
Net weight in lbs. (kg)	56 (25.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Hard-wired	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
<b>Installation notes</b>	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
<b>Standard accessories</b>	
Non-return flap	•
Reducer from 150 to 125 mm Ø	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z