

ELECTRONIC SPECIFICATIONS

Rated Output Voltage 2.5V Unbalanced 5V Balanced	Maximum Output Voltage 10V Unbalanced 20V Balanced	Maximum Input Voltage 10V Unbalanced 20V Balanced
Voltage Gain (all controls flat) Unbalanced: IN to OUT 0dB Balanced: IN to OUT 0dB	Frequency Response (all controls flat) +0, -0.5dB from 20Hz to 20kHz +0, -1dB from 10Hz to 100kHz	Signal To Noise Ratio 115dB (below rated output)
Total Harmonic Distortion 0.005% from 20Hz to 20kHz	Input Impedance 10k ohms Unbalanced 20k ohms Balanced	Output Impedance 500 ohms Unbalanced 1000 ohms Balanced
Equalizer Controls ±12dB at 25Hz, 50Hz, 100Hz, 200Hz, 400Hz, 1kHz, 3kHz, and 10kHz	Tilt Control ±6dB at 20Hz and 20kHz 650Hz Tilt Axis	

WEIGHTS & DIMENSIONS

Unit Dimensions (W x H x D) 17-1/2" (44.5cm) x 3-15/16" (10cm) x 15-11/16" (39.8cm)	Unit Weight 15 lbs (6.8kg)	Shipping Weight 29.5 lbs (13.4kg)
--	-------------------------------	--------------------------------------