

6000
series

integrated
amplifier

audiolab



Available in Silver and Black

SPECIFICATIONS

Model	6000A
General Description	Integrated amplifier
Design Philosophy And Core Technology	Support Bluetooth(aptX) / Phono(MM) In / trigger in and link / filter selection / USB upgrade
Analogue Input	3 x RCA , 1 x RCA Phono(MM) , 1 x RCA POWER IN
Digital Input	2 x coaxial , 2 x optical, Bluetooth(aptX)
Variable Output Voltage	0 – 2.3V
Preamp Output Impedance	120 ohm
Frequency Response (Line)	20Hz-20kHz (+/-0.3dB)
Frequency Response (Phono)	20Hz-20kHz (+/-0.5dB)
Signal-to-noise Ratio (Line)	>110dB (A-weighted)
Signal-to-noise Ratio (Phono)	>76dB (A-weighted)
DAC	ES9018K2M
Total Harmonic Distortion (THD)	<0.0005% (1kHz @ 0dBFS)
Frequency Response	20Hz-20kHz (+/-0.3dB)
Signal-to-Noise Ratio (S/N)	>110dB (A-weighted)
Crosstalk	<80dB (@ 10kHz)
Standby Power Consumption	<0.5W
Dimensions (W x H x D)	445 x 65.5 x 313 mm
Net Weight	7.9kg

