RP-6203F
FLOORSTANDING LOUDSPEAKER



LEGENDARY AMERICAN SOUND SINCE 1946
Klipsch Reference Premiere Series III is designed and engineered in the USA, where Klipsch has been crafting highly efficient, premium loudspeakers for over 80 years. Reference Premiere delivers immersive, high-resolution audio – powerful and precise sound for all your movies, music, and gaming.

ADVANCED ACOUSTICS
A two-way loudspeaker design, Klipsch Reference Series III features a new high-density axial Tractrix® horn-loaded tweeter with upgraded BMC material to reduce resonance, flush-mounted to the cabinet to minimize wave breakup and measurably improve off-axis response for a wider sweet spot. Reference Premiere copper-hued Cerametallic™ woofers provide impactful and enveloping bass, and the entire series is Dolby Atmos compatible for room-filling surround sound.

PREMIUM DESIGN
Sporting a knife edge cabinet for exceptional structural integrity, Klipsch Reference Premiere speakers feature clean lines and a sleek finish – complete with a flush-mount horn tweeter. Metal outrigger feet create increased stability and allow precise angle adjustment. Iconic copper details, a floating fabric grille, and an updated input panel complete the exceptional styling.

DEPTH CHARGE
Need to go lower? You can easily add a Klipsch Reference Premiere subwoofer to your system to further enhance the home theater experience – dropping the bass to the bottom! Choose from Reference Premiere Compact Subwoofers for a smaller footprint or go even deeper with Reference Premiere Ported Subs, both with the same legendary Reference Premiere aesthetics.

SPECIFICATIONS	
FREQUENCY RESPONSE	38-25kHz +/- 3dB
SENSITIVITY	96dB @ 2.83V / 1m*
POWER HANDLING (CONT/PEAK)	125W / 500W
IMPEDANCE	8 ohm (3.5 min @180Hz)
CROSSOVER FREQUENCY	1770Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Flush Mount BMC Axial Tractrix® Horn
LOW FREQUENCY DRIVER	Dual 6.5" Cerametallic Cone Woofers with Faraday rings
ENCLOSURE MATERIAL	MDF (Internally Braced)
ENCLOSURE TYPE	Bass Reflex via dual chamber rear-firing Tractrix® Ports
INPUTS	Dual binding posts / bi-wire / bi-amp
HEIGHT	39.60" (100.6 cm)
WIDTH	9.29" (23.6 cm)
DEPTH	17.57" (44.6 cm)
WEIGHT	54.9 lbs (24.9 kg)
FINISH	Ebony, Walnut

*SPL at 1M, half-space anechoic with 2.83V input, in-room sensitivity

FINISH TYPE	SKU	UPC	EAN
EBONY	1080635	743878093728	0743878093728
WALNUT	1080638	743878093735	0743878093735

All specifications are subject to change without notice. ©2026 Premium Audio Company, LLC, a wholly owned subsidiary of Gentex Corporation (NASDAQ: GNTX). Klipsch is a trademark registered in the USA and other countries, and is owned by Klipsch Group, Inc.