

Frequency Response

5 Hz – 100 kHz, +0/-3 dB

Distortion

THD: < 0.003% at 100 Hz

THD: < 0.005% at 20 kHz

IM: < 0.003%

S/N Ratio

> 116 dB, input shorted, IHF A-weighted

> 104 dB, input shorted, unweighted

Crosstalk

> 100 dB at 10 kHz

> 90 dB at 20 kHz

Input Impedance

Unbalanced: 30k Ω

Balanced: 30k Ω per leg

Output Impedance

Unbalanced: < 60 Ω

Balanced: < 60 Ω per leg

Input Sensitivity

200 mV for 1 V output

Total Gain: 14 dB

Maximum Output: 8 V

XLR Pin Identification

1 = Ground (Shield)

2 = Positive

3 = Negative (Return)

AC Power Requirement

110 – 120 V or 220-240 V, 50 – 60 Hz

(Set AC Voltage switch on rear panel)

25 watt standby; 30 watts when turned on

Dimensions

Width: 17 1/4" (437 mm)

Depth: 16" (406 mm)

Height, with feet: 5 7/8" (150 mm)

Height, without feet: 5 1/4" (133 mm)

Weight

Net: 24 lbs. (11 kg)

Shipping: 36 lbs. (16.4 kg)

Rack Mount Accessory

HRA 3 (May be purchased separately)

Specifications and features subject to change or improvement without notice.

© 2007, Parasound Products, Inc. Rev. 0.91