Product data sheet

HEATING TYPE	
Heating type	Induction
CONSTRUCTION TYPE	
Independent of oven	•
DESIGN	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless-steel frame	•
Surface-mounted installation	•
COOKING ZONE DETAILS	
Number of cooking zones	3
Number of cooking areas	0
Maximum number of pans	3
USER CONVENIENCE	
Operation via sensor controls	Smart Select
Display colour	Yellow
Pan and pan size recognition	•
Constant pan recognition	•

Recall function	•
Stop & Go function	•
Timer	•
Safety shut-off	•
Auto heat-up	•
Keeping warm	•
Individual setting options (e.g. audible signal tones)	•
Networking with Miele@home	•
Con@ctivity 3.0 automatic function	•
CLEANING CONVENIENCE	
Easy-to-clean ceramic glass	•
SAFETY	
SAFETY Safety shut-off	•
	•
Safety shut-off	
Safety shut-off Safety lock	•
Safety shut-off Safety lock System lock	•
Safety shut-off Safety lock System lock Integrated cooling fan	•
Safety shut-off Safety lock System lock Integrated cooling fan Overheating protection	•
Safety shut-off Safety lock System lock Integrated cooling fan Overheating protection Residual heat indicator	•
Safety shut-off Safety lock System lock Integrated cooling fan Overheating protection Residual heat indicator	• • • • • • 24 3/4 (626)
Safety shut-off Safety lock System lock Integrated cooling fan Overheating protection Residual heat indicator TECHNICAL DATA Dimensions in mm (width)	• • • • • • 24 3/4 (626)

Cutout dimension in mm (width) with surface- mounted installation	22 3/8 (567)
Cutout dimensions in mm (depth) with surface-mounted installation	20 1/2 (518)
Weight in lbs (kg)	30 (14)
Total rated load in kW	6.600-7.600
Voltage in V	0
Frequency in Hz	60
Dimensions in mm (height)	3 1/8 (78)

ACCESSORIES SUPPLIED

Power cable

1ST COOKING ZONE / COOKING AREA

Position	left centre
Туре	Dual-circuit ring
Max. rating in W	2600
Max. booster rating in W	3000
Size in mm	Ø 180–280
Max. TwinBooster rating in W	3,700

2ND COOKING ZONE / COOKING AREA

Position	rear right
Туре	Dual-circuit ring
Size in mm	Ø 140–190
Max. rating in W	1850
Max. booster rating in W	2500

Max. TwinBooster rating in W

3000

3RD COOKING ZONE / COOKING AREA

Position	front right
Туре	Dual-circuit ring
Size in mm	100-160 mm
Max. rating in W	1400
Max. booster rating in W	1700
Max. TwinBooster rating in W	2200