

30 271

ESSENCE

SINGLE-HANDLE PULL-OUT KITCHEN FAUCET DUAL SPRAY 1.75 GPM

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 13 1/16" Faucet height
- 12 3/8" Aerator height
- 8 1/16" Faucet reach
- Dual spray with toggle function: switches between regular water flow and spray without turning off the water
- 360° Swivel radius
- Weight operated pull-back mechanism for hose
- Integrated temperature limiter
- Adjustable flow rate limiter
- Forward rotating lever to prevent backsplash interference
- Solid metal spray
- GROHE QuickFix® Plus installation system
- 1.75gpm
- CALGreen compliant
- Compatible with GROHE Foot Control retro-fit set (30 310 000)



PRODUCT FEATURES:

-  GROHE StarLight®
-  GROHE SilkMove®

CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

- 30271000**  GROHE StarLight® Chrome
- 302712430**  Matte Black
- 30271A00**  Hard Graphite
- 30271DC0**  SuperSteel InfinityFinish™
- 30271GN0**  Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 06-03-2022

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

30 271

ESSENCE

SINGLE-HANDLE PULL-OUT KITCHEN FAUCET DUAL SPRAY 1.75 GPM

Pure Freude
an Wasser



TECHNICAL DATA:

Product Height	13-11/16 in
Product Length	9-13/16 in
Fitting Spout Height	12-6/16 in
Fitting Spout Reach	8-1/16 in
Fitting Handle Height	3-1/4 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min
Fitting No of Holes Required	1

