



Model	Bronze On-Wall 7G	Bronze AMS 7G
System Format	2-Way	2-Way
Frequency Response, In-Room (-6dB)	42 Hz - 30 kHz	83 Hz - 30 kHz
Sensitivity (2.83 Vrms @ 1m, Free-Field)	N/A	86 dB
Sensitivity (2.83 Vrms @ 1m, Installed)	88 dB	N/A
Nominal Impedance	8 Ohms	8 Ohms
Minimum Impedance (20Hz to 20kHz)	4.7 Ohms @ 17 kHz	3.7 Ohms @ 10 kHz
Maximum Peak SPL (AES75, Z-weighted)	112 dB	110 dB
Continuous Power Handling (CTA 426-B)	100 W	60 W
Recommended Amplifier Power (RMS, Music Signal)	50 - 200 W into 4 Ohms 30 - 100 W into 8 Ohms	30 - 120 W into 4 Ohms 10 - 60 W into 8 Ohms
Bass Alignment	Ported	Sealed
Port Tuning Frequency	47 Hz	N/A
Crossover Frequency	LF/HF: 3.0 kHz	LF/HF: 4.8 kHz
Drive Unit Complement	1 x 6" C-CAM bass mid driver 1 x 25mm C-CAM Gold Dome tweeter	1 x 4" C-CAM mid-range driver 1 x 25mm C-CAM Gold Dome tweeter with optimised waveguide
External Dimensions with all accessories fitted (H x W x D)	465 x 300 x 135 mm (185/16 x 1113/16 x 55/16 ")	173 x 185 x 302 mm (613/16 x 75/16 x 117/8 ")
Weight (Product, Each)	7.0 kg (15 lb 7 oz)	3.1 kg (6 lb 13 oz)

Learn more about Bronze Series 7G at monitoraudio.com/bronze

