# Product data sheet

## **CONSTRUCTION TYPE**

Built-in appliance	•	
Integrated appliance	•	
Door hinging	Left convertible	
Convertible hinging	•	
Can be installed side by side	•	

## **DESIGN**

**Lighting** BrilliantLight

## **USER CONVENIENCE**

FullAccess  EasyClean  MaxLoad hinge  DynaCool  SoftClose  SelfClose  Push2open  Networking with Miele@home  •	Freshness system	MasterFresh
MaxLoad hinge  DynaCool  SoftClose  SelfClose  Push2open  •	FullAccess	•
DynaCool • SoftClose • SelfClose • Push2open •	EasyClean	•
SoftClose • SelfClose • Push2open •	MaxLoad hinge	•
SelfClose • Push2open •	DynaCool	•
Push2open •	SoftClose	•
<u> </u>	SelfClose	•
Networking with Miele@home •	Push2open	•
	Networking with Miele@home	•

## CONTROLS

Eco mode •

10/19/23, 10:14 AM K 2912 Vi | Miele

2, 12, 22, 12, 11, 11, 11, 11, 11, 11, 1	7. 20 12 11 Million
User interface	MasterSensor
SuperCool	•
Number of temperature zones	2
Sabbath mode	•
FRIDGE / FRIDGE SECTION	
SlidingShelf	•
Door rack for tins	1
Height-adjustable tempered glass shelves	2
Number of vegetable drawers	1
Number of crisper drawers	2
Door rack for bottles	3
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•
SAFETY	
Overflow protection	•
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
TECHNICAL DATA	
Number of phases	1

10/19/23, 10:14 AM K 2912 Vi | Miele

Niche width in inches (mm), min.	36 (914)
Niche width in inches (mm), max.	36 (914)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 7/8 (629)
Appliance width in mm	35 3/4 (908)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	384 (173.8)
Door hinge technology	Fixed door
Door hinge technology  Max. weight of door, fridge section, in kg	Fixed door 82 (37)
Max. weight of door, fridge section, in kg	82 (37)
Max. weight of door, fridge section, in kg  Total usable capacity in I	82 (37) 20.55 (582) ft³ (l)
Max. weight of door, fridge section, in kg  Total usable capacity in I  Storage time in case of fault in h	82 (37) 20.55 (582) ft³ (I) 17
Max. weight of door, fridge section, in kg  Total usable capacity in I  Storage time in case of fault in h  Current consumption in milliamps (mA)	82 (37) 20.55 (582) ft <sup>3</sup> (l) 17 4000
Max. weight of door, fridge section, in kg  Total usable capacity in I  Storage time in case of fault in h  Current consumption in milliamps (mA)  Voltage in V	82 (37) 20.55 (582) ft <sup>3</sup> (l) 17 4000 110-120
Max. weight of door, fridge section, in kg  Total usable capacity in I  Storage time in case of fault in h  Current consumption in milliamps (mA)  Voltage in V  Fuse rating in A	82 (37) 20.55 (582) ft <sup>3</sup> (I) 17 4000 110-120

## **ACCESSORIES SUPPLIED**

Active AirClean filter

#### **APPLIANCE CATEGORY**

Refrigerator

## **AVAILABLE DISPLAY LANGUAGES**

10/19/23, 10:14 AM K 2912 Vi | Miele

Available display languages via Language Options

bahasa malaysia