

PE244INDXV

24" INDUCTION COOKTOP XV
BLACK GLASS



Experience instantaneous touch-through glass precision control

Select individual induction heating zones up to 2700 Watt performance reducing time-to-boil by up to 50%

Benefit from maximized cookware size accomodation
1 full surface bridge function setting with up to 5200 Watts with booster

Have full control over the cooking process with timer functions for each heating zone

Enjoy the utmost in easy cleaning of the tempered ceramic glass surface

PRODUCT FEATURES	
COOKTOP	
Maintop	4 induction zones
Heating zone power	Front Left Ø 7" 2000W (2500 W booster) Back Left Ø 7" 2000W (2700 W booster) Front Right Ø 7" 1400W (1800 W booster) Back Right Ø 7" 2000W (2700 W booster)
Controls	Touch-through-glass slider
Bridge function	Yes
Timer	Timed cooking function option for each induction zone
Power levels	9 + Booster
Stop & Recall function	Yes
Auto-Stop	Yes
Residual Heat Indicator	Yes
TECHNICAL SPECIFICATIONS	
Electrical supply	208-240 V 60 HZ - 7400 W 30 Amp dedicated circuit
Power connection	Hardwired with 40 3/16" power cord
Certification	ETL
Packaging dimensions and weight	W 25.98" H 23.23" D 6.10" 34.83 lbs

[illegible]

A cross-sectional diagram of a closed door. On the right side, there is an 'Air inlet' with a downward arrow. A large black arrow points left from the inlet, passing through a gap in the door frame. This arrow is marked with a large 'X'. Another arrow points left from the gap further to the left. A dashed line indicates the air flow path. The door is shown with a handle on the left and a lock on the right.

bertazzoni.com