DMP-A8 Master Edition Specifications

Basic Parameters

Model
DMP-A8 Master Gen 2

Display
8.6-inch LCD Touchscreen

Storage
8 GB DDR5 + 64 GB eMMC

DAC
AK4499EXEQ + AK4191EQ

Audio Processor
Eversolo AuralEngine

Operational Amplifiers
OPA1612

Power Supply
High-quality, low-noise dual power supply with separate linear and digital power sections

SSD Protocol
M.2 NVMe PCIe 3.0, 2280 form factor, supporting SSDs up to 8 TB

Ethernet
RJ-45 (10/100/1000Mbps)

WiFi
Dual-band Wi-Fi 6 (2.4G + 5G)

Music Services
TIDAL, Qobuz, HIGHRESAUDIO, Amazon Music, IDAGIO, Calm Radio, Internet Radio, TuneIn, Radio, Paradise, Deezer, SoundCloud, Presto Music, Apple Music...

Music Streaming
Spotify Connect Lossless, TIDAL Connect, Qobuz Connect, DLNA, Network Audio Adapter, and more...

Audio Inputs & Outputs

USB-A Audio Input
USB3.0 * 2

Bluetooth Input
Bluetooth 5.4

USB-B Audio Input
USB compatibility: Windows 10/11, macOS, Android, and iOS. Supports up to stereo DSD512 and PCM 768kHz/32bit.

Optical/Coaxial Input
Supports up to stereo PCM 192kHz/24bit and DSD64 via DoP.

ARC Input
Supports up to stereo PCM 192kHz/24bit.

Analog Audio Input
XLR balanced + RCA pre-input. Input range: RCA maximum 2.1 Vrms; XLR maximum 4.2 Vrms.

USB Audio Output
Supports up to stereo Native DSD512 and PCM 768kHz/32bit. Compatible only with UAC-compliant USB DACs.

IIS Audio Output
Supports up to stereo Native DSD512 and PCM 768kHz/32bit.

Optical/Coaxial Output
Supports up to stereo PCM 192kHz/24bit and DSD64 via DoP.

Analog Audio Output
XLR balanced + RCA pre-output.

Audio Characteristics

XLR Output Audio Characteristics
Output Level: XLR 4.2 V
Frequency Response: 20 Hz–20 kHz, XLR/RCA ±0.25 dB
THD+N: 0.000075% (-122 dB)
Dynamic Range: XLR >129 dB
SNR: XLR >129 dB
Crosstalk: XLR >133 dB

RCA Output Audio Characteristics
Output Level: RCA 2.1 V
Frequency Response: 20 Hz–20 kHz, XLR/RCA ±0.25 dB
THD+N: 0.000086% (-121 dB)
Dynamic Range: RCA >127 dB
SNR: RCA >127 dB
Crosstalk: RCA >131 dB

Other Information

Control Methods
On-screen Touch Control, Eversolo Control App, and Remote Control

Power Supply
AC 100–240 V, 50/60Hz

Rated Power
30 W

Dimensions
388 × 265 × 98.5 mm (L × W × H)

Packing List
Remote Control × 1, Power Cable × 1, Product Manual × 1

Net Weight
6 kg

Gross Weight
8.45 kg