

Specifications

Speaker Design

2-Way

Woofer [in, mm]

4, 100

Tweeter [in, mm]

½, 13

Rated Impedance [Ω]

4

Recommended Amplifier Power [Watts RMS]

15-75

Sensitivity [1W, 1m]

88

Frequency Response [Hz]

60-20k

Mounting Hole Diameter [in, mm]

3-11/16, 94

Top Mount Depth [in, mm]

1-13/16, 46

Bottom Mount Depth [in,mm]

2-1/16, 51

Tweeter Protrusion [in,mm]

1/8, 3

Grilles

Yes

Tweeter Magnet Material

Neodymium

Tweeter Dome Material

Silk

Woofer Cone Material

Polypropylene

Woofer Surround Material

Rubber

Support



Manuals

2020 KS Series | Multilingual | Download (</app/manuals/47KSC.pdf>)

Do you have a different model? [Click Here \(/product-manuals\)](/product-manuals)



Support Links

[Subwoofer / Speaker FAQ \(/faq\)](/faq)



Contact Support

Technical Support

(405) 624-8583 (tel:+14056248583)

8am - 5pm CST

support@kicker.com (<mailto:support@kicker.com>)

Warranty Support

(405) 624-8510 (tel:+14056248510)

8am - 5pm CST

warranty@kicker.com (<mailto:warranty@kicker.com>)



Sign up for offers

(</subscribe>)

(<http://www.facebook.com/KICKERaudio>)