

UMD10N



Colour range
Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



Optional RAL – RA



Brass – G



Copper – P



Chrome – C



Burnished – B

Finishes
Knobs, handles, frames

Optional solid door version



optional +

Order code: add letter "Q" before the "N" letter

Available ovens

Electric oven	
Primary oven:	Secondary oven:
UOV 60 E3 TFT S	UOV 30 E3 TFT
Maximum input: 3.5 kW	Maximum input: 2.5 kW


Configurations

6 burners with fry top*	Induction
	

Electric oven	UMD10FDNS3	UMD10NS3
	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished

Fuel requirements	Natural gas / Liquid propane Voltage: 240 Volts Amps: 27.7	All electric Voltage: 240 Volts Amps: 75.6
		<i>*Insufficient amperage may lower heating performance when multiple functions are being used at the same time</i>

Consumption

 Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW	 Induction zone Ø 5" 3/4 1.4 / 1.8 kW	 Induction zone Ø 7" 1/4 1.85 / 2.5 kW	 Induction zone Ø 8" 11/16 2.3 / 3.2 kW	 Double ring Dual burner 20000 btu/h / 900 btu/h	 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h
 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h				

Complements & accessories	Hood	UAM100	Ladle holder panel	AM4-100
---------------------------	------	--------	--------------------	---------

Technical drawing & dimensions

