

Technical specifications



Model	Bronze 50 7G	Bronze 300 7G	Bronze Centre 7G
System Format	2-Way	2.5-Way	2-Way
Frequency Response, In-Room (-6dB)	41 Hz - 30 kHz	34 Hz - 30 kHz	50 Hz - 30 kHz
Sensitivity (2.83 Vrms @ 1m, Free-Field)	86 dB	88 dB	88 dB
Sensitivity (2.83 Vrms @ 1m, Installed)	N/A	N/A	N/A
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms
Minimum Impedance (20Hz to 20kHz)	4.0 Ohms @ 200 Hz	4.4 Ohms @ 38 Hz	4.3 Ohms @ 200 Hz
Maximum Peak SPL (AES75, Z-weighted)	112 dB	118 dB	119 dB
Continuous Power Handling (CTA 426-B)	100 W	150 W	120 W
Recommended Amplifier Power (RMS, Music Signal)	50 - 200 W into 4 Ohms 30 - 100 W into 8 Ohms	75 - 300 W into 4 Ohms 40 - 150 W into 8 Ohms	60 - 240 W into 4 Ohms 30 - 120 W into 8 Ohms
Bass Alignment	Ported - HiVe II	Ported - HiVe II	Sealed
Port Tuning Frequency	47 Hz	38 Hz	N/A
Crossover Frequency	LF/HF: 3.0 kHz	LF/MF: 470 Hz MF/HF: 2.6 kHz	LF/HF: 2.7 kHz
Drive Unit Complement	1 x 6" C-CAM bass mid driver 1 x 25mm C-CAM Gold Dome tweeter	2 x 6" C-CAM bass mid driver 1 x 25mm C-CAM Gold Dome tweeter	2 x 6" C-CAM bass mid driver 1 x 25mm C-CAM Gold Dome tweeter
External Dimensions with all accessories fitted (H x W x D)	335 x 185 x 328 mm (133/16 x 75/16 x 127/8 ")	1005 x 269 x 392 mm (399/16 x 105/8 x 157/16 ")	205 x 500 x 229 mm (81/16 x 191/16 x 9 ")
Weight (Product, Each)	6.4 kg (14 lb 2 oz)	15.6 kg (34 lb 6 oz)	8.1 kg (17 lb 14 oz)

Available Finishes



White



Black



Walnut