## Specs & Details

**Dimensions: 59 1/2 H x 24 W x 24 D** 

## **APPEARANCE**

Color Appearance	Gray	
Installation	Free-Standing	
CAPACITY		
Unit Capacity	40 Gallons	
ECONOMICAL / QUIET		
Operating Sound Level	41 dBA	
FEATURES		
Anode Rod	Sensing Magnesium	
Communication	Yes	
Connected Capabilities	Amazon Alexa Google Home	
Control Type	Electronic  LED  Service Diagnostics Integrated	
Demand Response Capable	<u>Yes</u>	

Diagnostic Feedback	Filter, Lock, Standard Electric
Drain Valve	Left Side
Drain Valve Type	Brass
Electronic, Integrated Mixing Valve	Yes
Fuel Type	Electric
Operating Modes	Hybrid (Default Mode) Heat Pump High Demand/Boost Standard Electric
Power Cord Length	6' 3-prong
Product Type	Electric Heat Pump
Renewable Air Filter	Top of Unit
Sensor	Leak Sensor Included (SPLK10N01A)
Temp & Pressure Relief Valve	Right Side
Temperature Setting	100-140° F Range
Temperature Setting Factory Default	120° F

UEF	3.1	
Water Connection Location	Тор	
WiFi Connect	Built-In	
POWER / RATINGS		
Electrical Circuit Required	120/110VAC 15A, 60HZ or 240/208VAC 25A, 60Hz	
Electrical Consumption - Lower Element	3600W at 240VAC 900W at 120VAC	
Electrical Consumption - Upper Element	3600W at 240VAC 900W at 120VAC	
Energy Consumption (kWh/year)	724	
First Hour Rate (FHR)	46 Gallons	
<u>Hertz</u>	60	
Operating Water Pressure	20-125 PSI (30-80 PSI recommended)	
WARRANTY		
<u>Labor Warranty</u>	Limited 1-year entire appliance	
Parts Warranty	Limited 10-year tank and parts	

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	<u>194 lb</u>
Connection Sizes - Hot Water Outlet (MNPT)	3/4"
Connection Sizes - Water Inlet (MNPT)	3/4"
Net Weight	<u>165 lb</u>
Overall Depth	24 in
Overall Height	59 1/2 in
Overall Width	24 in
Product Diameter	24 in
Product Height (to top of unit)	57 3/4 in
Product Height (to top of water inlet/outlet connections)	59 1/2 in