10/19/23, 3:50 PM DA 2588 | Miele

Product data sheet

CONSTRUCTION TYPE	
Extractor unit	•
DESIGN	
Colour	Stainless steel
RAL colour possible as customization on request	•
Customization possible on request	•
OPERATING MODES	
Recirculation conversion kit (order separat	ely)DUU 151
Active charcoal filter (order separately)	DKF15-900
Type of air guide	Convertible
USER CONVENIENCE	
Electronic controls	•
Power levels (excluding booster level)	3
Programmable booster level switch-off	•
Run-on time 5 / 15 min	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Programmable active charcoal filter saturatindicator	tion •

10/19/23, 3:50 PM DA 2588 | Miele

	5/12000 Initials
Easy-to-clean CleanCover hood liner	•
Networking with Miele@home	•
FILTER SYSTEM	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
LIGHTING	
LED	•
Number x W	2 x 3 W
Light intensity in Lx	300 lx
Colour temperature in K	3000 Kelvin
FAN	
Dual-action fan	•
AC motor	•
VENTED	
Air throughput and sound emissions	Values upon request
SAFETY	
Safety shut-off	•
TECHNICAL DATA	
Canopy width in mm	31 5/8 (802)

10/19/23, 3:50 PM DA 2588 | Miele

,	·
Canopy height in mm	2 (50)
Canopy depth in mm	15 7/8 (402)
Minimum height above electric cooktops in mm	24 1/8 (610)
Minimum height above gas cooktops (max. 12.6 kW total output, burner ≤ 4.5 kW) in mm	26 (660)
Net weight in kg	27 (12.1)
Length of power cable in m	2 (0.8)
Standard plug fitted	•
Total rated load in kW	0.356
Voltage in V	120
Fuse rating in A	15
Frequency in Hz	60
Number of phases	1

IN

Vent connection at top	•
Diameter of exhaust duct in mm	6 (150)

ACCESSORIES SUPPLIED

RF Con@ctivity 2.0 transmitter for CM XKS 3000 Z