# Panamax MD2-C



Surge



Noise



Picture & Sound **Improve** 



Connected Equipment



Lifetme Narranty

### Applications for:

- TVs
- Plasmas/LCD's
- DVD/DVR Players
- Cable Modems
- HDTV Tuners



AC & Coaxial

#### **Protection**


- EMI/RFI Filtration Circuitry for Clean, Unimpeded Power.
- Protect or Disconnect<sup>™</sup> Circuitry
- Premium Power Filtration Improves Picture & Sound.
- One Pair of Universal CATV/SAT/ANT Connectors.
- Two Diagnostic Lights (LED) Power On/Protection OK and Line Fault
- Thin Profile Only 1.5 inches deep.
- Two AC Outlets
- 4 ft. Coax Cable
- Removable, Paintable Cover







Front cover can easily be removed & painted to match any wall color.



## **SPECIFICATIONS**

AC POWER	
Protect or Disconnect™ Circuitry	Yes
Line Voltage	120VAC, 50/60Hz
Initial Clamping Level	200V
Voltage Protection Rating (UL144	19 3rd Edition, 3,000A)
L-N 400V,	L-G 500V, N-G 400V
Nominal Discharge Current	3,000A
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
EMI/RFI Noise Filtration	_ 50dB (100kHz - 1 MHz)

Response Time	< 1 nanosecond
Single Pulse Energy Dissipation	1350 Joules
Peak Impulse Current	60,000 A
Catastrophic Surge Circuit	Yes
Thermal Fusing	Yes
Coax Specifications:	
CATV / Sat Clamping Level	75V
Frequency Range	0MHz - 2.2GHz
Insertion Loss	<.5 dB
Connections	Female "F"

Design and specifications subject to change without notice due to product improvement.

#### MEASUREMENTS, WEIGHTS, QTYS & UPC FOR ORDERING & SHIPPING

	Measurements	Weights	Qty.	UPC
Product:	1.625" x 3.25" x 5.25"	.65 lb.	1	-
Individual Box:	3" x 4.75" x 6.25"	.75 lb.	1	050616008778
Inner Pack:	6.125" x 15' x 6.375"	5 lbs.	6	30050616008779
Master Pack:	15" x 10" x 13"	21 lbs.	24	50050616008773

800-472-5555 • www.panamax.com

