

UP48W



Colour range

Body



Blue
grey – BG



White – WH



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Optional RAL – RA

Finishes

Knobs, handles



Satin

Optional solid door version




optional +

Order code: change letter "W" with "Q"

Available ovens

Electric oven	
Primary oven:	Secondary oven:
UOV 80 M	UOV 30 E
Maximum input: 3.7 kW	Maximum input: 2.5 kW

Configurations


5 burners with fry top* and coup de feu	8 burners with fry top*	Induction
		

Electric oven	UP48FSWMP Brushed	UP48FWMP Brushed	UPI486WMP Brushed
---------------	----------------------	---------------------	----------------------

Fuel requirements	Natural gas / Liquid propane Voltage: 240 Volts Amps: 25.8	Natural gas / Liquid propane Voltage: 240 Volts Amps: 25.8	All electric Voltage: 240 Volts Amps: 73.8
-------------------	--	--	--

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW	 Induction zone Ø 5" 3/4 1.4 / 1.8 kW	 Induction zone Ø 7" 1/4 1.85 / 2.5 kW	 Induction zone Ø 8" 11/16 2.3 / 3.2 kW	 Coupe de Feu 5500 btu/h	 Double ring Dual burner 25000 btu/h / 900 btu/h
 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h		

Complements & accessories

Hood	UAGQ48	Ladle holder panel	AM4-120
------	--------	--------------------	---------

Technical drawing & dimensions

