


PTAC PDE09K3SG

Cooling BTU: **9400/9200**
Heating BTU: **17000/11700/8300**
EER: **12.1/12.1**

Volts: **230/208**



Unit Dimensions

Height: **16"**
Width: **42"**
Depth: **13 3/4"**

Additional Measurement Specs

Front Cover Height: **16"**
Front Cover Width: **42"**
Front Cover Depth: **7 3/4"**
Cut-Out Height: **16 1/4"**
Cut-Out Width: **42 1/4"**
Dimensions With Package: **21 1/2"**
Net Weight: **115 lbs**
Shipping Weight: **135 lbs**

Detailed Electrical Information



Voltage: **230/208**
Volt Range: **253-187**
Cooling Amps: **3.7/3.9**
Cooling Watts: **775/760**
Reverse Heating Amps: **21.8/19.7/15.0/13.6/10.7/9.7**
Reverse Heating Watts: **5000/3450/2450**
Compressor LRA: **19.5**
Compressor RLA: **3.5**

Additional Performance Specs

Air Circulation: **300 CFM**
Moisture Removal: **2.1 pints per hour**
Indoor CFM High: **355**
Indoor CFM Low: **325**
Sensible Heat Ratio: **0.85**
Vent CFM: **75**
R-410A Charge: **24 oz**
Suggested Retail Price: Please contact the Friedrich Contract Sales Department at (800) 541-6645