



Tumble dryer

T7HXLW.U

7-series

Capacity: 11 kg

Condenser with heat pump

Number of programs: 20

Auto condenser filter cleaning

ADA Compliant: Yes, standing on the ASKO pedestal drawer

Installation: Freestanding



Construction and performance

- Inner drum: Stainless Steel
- Motor: Long life and quiet brushless motor
- Heating system: Heat pump
- Drying types: Sensor or time controlled
- Drum volume: 5.2 Cubic ft
- Shortest program time: 30 min
- Easy to use lint filter: Yes, Asko double lint filter

Use and flexibility

- Water tank volume: 6.5 l
- Automatic programs: Yes
- Door opening diameter: 340 mm
- Door maximum opening angle: 180 °
- Sensors: Moisture sensor
- Auto condenser filter cleaning: Yes
- Load Light™ - Illumination of the drum: Yes

Interaction and control

- Remaining time indicator: Yes
- Type of display: TFT - Full colour touch display (possible to interact with jog dial as well)
- Indication when program is ready: Yes
- Language settings: Chinese simplified, Chinese traditional, Swedish, Slovenian, Slovak, Russian, Polish, Norwegian, Dutch, Latvian, Lithuanian, Japanese, Italian, Croatian, French, Finnish, Estonian, Spanish, English, German, Danish, Czech

Programs and options

- Number of programs: 20
- Drying programs: Auto normal dry, Wool, Time program, Conditioning, SportWash, Steam refreshing, Steam wrinkle care, Shirts, Bedding, Drum cleaning, Antiallergy, Jeans, Quick pro cotton, Down/bulky items, Mixed laundry, Synthetics, Delicate, Cotton iron, Cotton storage, AirRefresh
- Settings: Load level setting, Steam programmes (Steam wrinkle care and Steam refresh), Delayed start, Low temperature option, Setting of dryness level, Timed drying, Anti-crease function, Half load, Pause, Disinfection mode, Beep indicating that program is ended, Quick dry

Design and integration

- Door hinge placement: Right/Left
- Adjustable feet: 15 mm
- ASKO dryer and washer can be easily stacked.: Yes, on XL WM
- Loading type: Front load

Safety and maintenance

- Child lock on display: Yes
- Overheat protection: For motor and electronics

Technical data

- Noise level drying dB(A): 61
- Power consumption in standby mode: 0.39 W
- Consumption in off mode: 0.22 W
- Plug type: USA
- Connected load: 2000 W
- Voltage (V): 208-240 V
- Number of phases: 1
- Fuse: 30 A
- Frequency: 60 Hz
- Net weight: 61.3 kg
- ISO 14001 certified manufacturing: Yes

Dimensions

- Width: 595 mm
- Height: 850 mm
- Depth: 746 mm
- Depth with door open: 1165 mm
- Length of electrical cord: 2100 mm

Logistic information

- Packaging width: 620 mm
- Packaging height: 925 mm
- Packaging depth: 860 mm
- Gross weight: 66.5 kg
- Product code: 746425
- EAN code: 3838783003270

