


- The Captur[™] system's advanced blower design features a forward positioned centric inlet to remove smoke and odor faster. Three-speed blower control exhausts at a powerful 600 CFM.
- Forward placement and smooth-flow blower wheel design ensure quiet,
 0.8 sone operation at normal speed.
- Bright, two-level LED modules supported by a 3-year warranty illuminate evenly and are tested in cooking environments to ensure long life without dimming. ENERGY STAR® qualified LEDs maximize savings.
- Tap-touch, 3-speed capacitive control features a smooth, easy-to-clean surface.
- Dishwasher-safe, hybrid baffle filters provide ultra-efficient grease removal with superior air flow. The filter clean reminder ensures they will always maintain a high level of capture.
- EZ1 brackets enable single-person installation in less than half the time of traditional methods.
- ADA compliant, remote operation is possible using a standard UL approved wall switch (kit sold separately).
- Non-duct capable with use of charcoal filters, sold separately. Hidden louvers on top of hood exhaust away from cabinetry.



SPECIFICATIONS						OPTIONAL ACCESSORIES		
Width	Blower CFM	Normal Sones	Volts	Amps	Duct	Non-Ducted Charcoal Filter	ADA Electronic Adapter Kit*	Make-Up Air Dampers
30"	600	0.8	120	1.9	3-1/4" x 14" or 7" RD Optional 3-1/4" x 10"	HPF24 (Type Xb)	- HAWRK3	MD6TU, MD8TU, MD10TU
36"						HPF30 (Type Xc)		
36" 42"						HPF36 (Type Xd)		
48"						HPF42 (Type Xe)		

^{*} Kit sold separately.