Specifications

Power requirements	
Mains Power Supply	AC 100~240 volts, 50Hz - 60Hz DC 12V 1.5A only (switching adaptor)
Remote Control Battery	UM-4 (AAA) * 2
Frequency Coverage	
Region A (Most countries)	FM: 87.5-108, 100kHz
Region A (Philippines, Romania)	AM: 522-1710, 9kHz
Region B (US, Mexico, Canada)	FM: 87.5-107.9, 200kHz
Region B (US, Mexico, Canada)	AM: 520-1710, 10kHz
Region C (Most countries)	FM: 87.5-108, 50kHz
Region C (SE Asia)	AM: 522-1620, 9kHz
Region D (Brazil, Japan)	FM: 76-108, 100kHz
Region D (Brazil)	AM: 522-1629, 9kHz

Internal Antenna system	AM built-in ferrite antenna
	FM built-in telescopic antenna
External antenna terminal	AM antenna screw terminal
	FM F-type antenna terminal
Output power	7W 10% T.H.D.@100Hz
Headphones socket	3.5mm diameter stereo jack
	output power 1mW + 1mW (load 32ohm)
Aux In socket	3.5mm diameter stereo jack.
	Input sensitivity: In 280mVrms, Output 7W @ 100Hz
	Input impedance: 47K ohm
REC out	Output impedance: 22K ohm
DC IN	12V / 1.5A center pin positive
Dimension	W x H x D in inches: 9.4 x 4.5 x 7.2
Weight	5.7lbs

※ The barcode label on the product is defined as below:	
aH181200001	