

SBC7BRSIFNCF2LHD



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved nitro coffee dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes panel-ready door, adjustable legs, and caster set for optional mobility

Highlights:

Made in Europe

Dual tap system lets you serve cold brew coffee from two separate kegs

Panel-ready door lets you customize the unit to best match your style

Product Features:

24" Wide Nitro Coffee Dispenser	Kegerator includes all of the equipment you need to serve nitro coffee from two sixtel kegs		
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA		
Versatile use	Approved for both residential and commercial settings		
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use		
Panel-ready door	Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)		
Complete cold brew tap kit included	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs		
Dual tap system	Commercial grade tap kit includes a dual tap stainless steel stout style draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs		
Slim counter height dimensions for rece or freestanding use	ssed Ideal 24" footprint for an easy fit		
Height adjustable	Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter		
SUMMIT APPLIANCE DIVISION, FELIX STO 770 Garrison Avenue Bronx, NY 10474 USA TEL			



SBC7BRSIFNCF2LHD Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	22.38" (57 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Integrated Frame
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	121.0 lbs. (55 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106304
Kegerator	
Door Swing	LHD
Reversible	No
Height Adjustable	Yes
Tap Kit	Yes
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Glass and Scalloped
Shelf Qty	4
Thermostat Type	Dial
Interior Light	Yes
Refrigerant	R600a
	0.64 oz.
Refrigerant Amount	
Refrigerant Amount Inter Height	27.75" (70 cm)
•	27.75" (70 cm) 21.0" (53 cm)
Inter Height	

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F



