



# **DS Series 4x6" Coax**

The DS 4x6-Inch Coaxial Speakers are a great way to get top-notch sound in your doors.

Using zero protrusion PEI tweeters ensures you get every bit of clarity you need, without interfering with factory grilles.

These DS speakers work best with 30 watts of recommended power. See below for more details.

# **Specifications**

Model	
DSC460	
Speaker Design	
2 - Way	
Woofer [in, mm]	
4x6, 100x160	
Mid [in, mm]	
n/a	
Tweeter [in, mm]	

1/2, 13

#### Rated Impedance $[\Omega]$

4

# Peak Power (watts, per ANSI/CTA-2031-A)

120

## **Recommended Amplifier Power (watts RMS)**

30

#### Sensitivity [1W, 1m]

88

# Frequency Response [Hz]

50-20k

# Mounting Hole Diameter [in, mm]

4x6, 101x152

#### Top Mount Depth [in, mm]

5/16, 7

#### **Bottom Mount Depth [in, mm]**

1-11/16, 43

#### **Tweeter Protrusion [in, mm]**

0

#### **Grilles**

No

#### **Tweeter Magnet Material**

Neodymium

#### **Tweeter Dome Material**

PEI (polyether imide)

#### **Tweeter Design**

Balanced dome

## **Woofer Cone Material**

Polypropylene

#### **Woofer Surround Material**

Polyester foam

# **Support**



# **Manuals**

2016 DS Coaxials | Multilingual | Download (/app/manuals/mids\_tweets/ds/2016\_DSC\_Coax\_Rev\_C.pdf)