

Specifications

Model	Zone Controller ZC1(W)CZM	Zone Controller ZC1(B)CZM	Zone Controller ZC1(W)CZC	Zone Controller ZC1(B)CZC
Amplifier Compatibility				
Colour	White (RAL9003)	Black (RAL9005)	White (RAL9003)	Black (RAL9005)
External Dimensions (H x W)	86.79 x 86.79mm (3.42 x 3.42in)		115.1 x 70.6mm (4.53 x 2.78in)	
External Dimensions, Depth [From rear side of mounting plate to outer side of shield box]	23.7mm (0.93in)		23.1mm (0.91in)	
External Dimensions, Depth [From tip of rotary encoder dial to outer side of shield box]	42.8mm (1.68in)		42.8mm (1.68in)	
Mounting Holes, Distance (Center to Center)	60 mm (2.36in)		83.5mm (3.29in)	
Weight	120g (4.2oz.)		120g (4.2oz.)	
Operating Temperature Range	0-40°C (32-104°F)			
Display Screen Dimension (excluding black border)	27.72mm x 27.72mm			
Display Screen Area (excluding black border)	768.4sqmm			
Display Screen Resolution	240 x 240 pixels			
Display Screen Type	RGB, Transmissive / Normally Black			
Display Screen Material	High gloss polished transparent acrylic			
Exterior & Mechanical Parts Material	Plastic (ABS-PC)			
Base Construction & Shield Material	Pre-galvanized steel			
Power Consumption	PoE Class 1 / 3.84 Wmax			
Power Supply	Power to the RJ45 Ethernet port on the rear of device using a category 5e cable (or faster STP) with the use of a standard PoE switch, or PoE injector			
Standby Modes	6 settings available: 30 secs, 2 mins, 5 mins, 15 mins, 30 mins, 60 mins			
Connection & Data Protocol	RJ45, proprietary over CAT 5e (or faster STP)			
Maximum Cable Length (CAT 5e)	100m (328ft)			
IP Rating	IP 30			
Warranty Period	2 Years			

© Copyright 2025 Premium Audio Company Technology Center K.K. All rights reserved.

© 2025 Premium Audio Company Technology Center K.K. Tous droits de reproduction et de traduction réservés.

Copyright ©2025 Premium Audio Company Technology Center K.K., a wholly owned subsidiary of Gentex Corporation (NASDAQ: GNTX).

O2506-0 SN 29404227