AT-SP3X Speaker

Speaker Unit	76 mm (3.0") dia. x 2
Tweeter Unit	27 mm (1.1") dia. x 2
Maximum Output	30W
Frequency Response	55 to 20,000 Hz
Communication System	Compliant with Bluetooth standard Ver. 5.3
Maximum RF Output	10 mW EIRP
Maximum Communication Range	Line of sight - approx. 10 m (33')
Frequency Band	2.4 GHz band (2.402 GHz to 2.480 GHz)
Modulation Method	GFSK, Pi/4DQPSK, 8DPSK
Spread Spectrum Method	FHSS
Compatible Bluetooth Profiles	A2DP
Support Codec	SBC
Supported Content Protection Method	SCMS-T
Supported Sample Rates	44.1 kHz, 48 kHz
Supported Bit Rates	16 bit, 24 bit
Transmission Band	20 to 20,000 Hz
Power Supply	AC100-240V / DC18V (using supplied AC adapter)
Input Jack	Analog audio input terminals (RCA pin plug x 2)
Speaker Cord Length	2.0 m (6.6')
AC Adapter Cord Length	1.2 m (3.9')
Dimensions	200 mm (7.9") x 125 mm (4.9") x 136 mm (5.4") (H x W x D) (excluding protrusions)
Weight	Left Side: Approx. 1.5 kg (3.3 lbs) Right Side: Approx. 1.6 kg (3.5 lbs)
Operating Temperature	5°C to 40°C (41°F to 104°F)
Accessories Included	AC adapter, AC adapter replacement plug x 4, speaker cable (for L/R connection), rubber foot x 8
Notes	For product improvement, the product is subject to modification without notice.