

DUAL FUEL SELF-CLEAN RANGE

RVDR330-5B – 30" WIDE



Features and Functions

- Wide variety of BTU ratings to accommodate all types of surface cooking needs – including a fifth burner
 - Left front – 18,000 BTU
 - Left rear – 8,000 BTU
 - Center – 9,000 BTU
 - Right front – 17,000 BTU
 - Right rear – 12,000 BTU
- Sealed burners with porcelainized, cast-iron burner caps
- **Exclusive** – SureSpark™ Ignition System
- Automatic electric spark ignition/re-ignition; surface burners light at any position on the knob and re-light if extinguished even on lowest setting
- **Exclusive** – largest oven cavity in the industry
 - 4.7 cu. ft. overall
 - 4.1 cu. ft. measured to AHAM standard(See specifications chart for oven interior dimensions)
- High performance cooking modes include Bake, Convection Bake, TruConvect™ Convection Cooking, Convection Roast, Hi Broil, Medium Broil, Low Broil, Convection Broil, Convection Dehydrate, and Convection Defrost
- **Exclusive** – Patented Vari-Speed Dual Flow™ Convection System has the largest convection fan in the industry; the 8 1/2" fan works bi-directionally for maximum airflow and excellent cooking results
- Concealed 10-pass dual bake element provides precise temperature control



30" Wide Dual Fuel Self-Clean Range
(Shown with optional 6" H. backguard)

- 10-pass broiler with heat reflector provides superior broiling performance
- Rapid Ready™ Preheat provides super fast preheating
- Oven has six porcelain-coated rack supports and comes standard with one TruGlide™ full extension oven rack and two standard racks
- Halogen oven lighting provides excellent visibility throughout oven cavity
- Shipped standard with island trim
- Accessory portable griddle/grill (RDPGD) available for use over center burner

Easy Operation and Cleanup

- Extremely large self-clean convection oven
- Permanently sealed burners – spills cannot enter the one-piece tooled and porcelainized burner box
- Durable metal die-cast knobs with child-proof, push-to-turn safety feature
- Customer removable knobs, grates, and burners/caps for easy cleaning
- Continuous grate design for easy movement of pots and pans

Installation Accessories

- 6" high backguard (RD30BG6)
- High shelf (RD30HS24)
- Countertop side trim (P24CST)
- Countertop rear trim (P30CRT)
- Curb base and custom curb base front (P30CBF4)
- LP conversion kit (RDLPKR3)
- Natural conversion kit (RDNKR3)

Finishes

- Available in Stainless Steel (SS), Black (BK), and White (WH)



Warranty Highlights

- Three-year full – complete product
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – stainless steel exterior
- Ten-year limited – porcelain oven
- Five-year limited – surface/tube burners



DESCRIPTION	DUAL FUEL SELF-CLEAN 30" WIDE RANGE
	RVDR330-5B
Overall Width	29 7/8" (75.9 cm)
Overall Height	To top of side trim – 35 7/8" (91.1 cm) minimum; 37" (94.0 cm) maximum Legs adjust – 1 1/8" (2.9 cm)
Overall Depth from Rear	To front of side panel – 25" (63.5 cm) To front of door – 25 3/4" (65.4 cm) To front of control panel – 27 1/8" (68.9 cm) To end of knobs – 29" (73.7 cm)
Additions to Overall Height	To top of island trim – add 0" (0.0 cm) To top of 6" h. backguard – add 6" (15.2 cm) To top of high shelf – add 18 3/16" (46.2 cm)
Gas Requirements	Ships Natural or LP/Propane; Field convert with conversion kit (purchased separately); accepts standard residential 1/2" (1.3 cm) ID gas service line.
Gas Manifold Pressure	Natural 5.0" W.C.P./ Liquid Propane L/P 10.0" W.C.P.
Electrical Requirements	240-208 VAC 60 Hz electrical connection box on product, connect with locally supplied 3-wire, flexible cord or "pigtail" rated 40 amp. 125-250 VAC minimum. Cord must be agency approved for use with household electric ranges.
Maximum Amp Usage	240V – 25.4 amps; 208V – 22.9 amps
Surface Burner Rating Natural/LP	Left Front: 18,000 BTU Nat./15,800 BTU LP/Propane (5.3 kW Nat./4.7 kW LP/Propane) Left Rear: 8,000 BTU Nat./7,200 BTU LP/Propane (2.3 kW Nat./1.9 kW LP/Propane) Center: 9,000 BTU Nat./8,000 BTU LP/Propane (2.7 kW Nat./2.3 kW LP/Propane) Right Front: 17,000 BTU Nat./15,000 BTU LP/Propane (5.0 kW Nat./4.4 kW LP/Propane) Right Rear: 12,000 BTU Nat./10,800 BTU LP/Propane 3.5 kW Nat./3.2 kW LP/Propane)
Oven Interior Width	25 5/16" (64.6 cm)
Oven Interior Height	16 1/2" (41.9 cm)
Oven Interior Depth	Overall – 19 1/2" (49.5 cm) AHAM* – 16 13/16" (42.7 cm)
Oven Volume	Overall – 4.7 cu. ft. AHAM* – 4.1 cu. ft.
Approximate Shipping Weight	410 lb. (184.5 kg)

*The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.



Viking Range, LLC | 1-888-845-4641 or 662-455-1200

For detailed product information, model numbers, or to request a quote visit vikingrange.com

© 2013 Viking Range, LLC | Specifications subject to change without notice.