



Color Variants

CMP250130
Glass front in Gaggenau Silver
Width 60 cm
CMP250100
Glass front in Gaggenau Anthracite
Width 60 cm
CMP250110
Glass front in Gaggenau Metallic
Width 60 cm

Included accessories

1 x measuring spoon.
1 x assembly screws.
1 x milk container.
1 x descaling container.
1 x test strip.
1 x connection hose for milk frother.

CMP250130
Glass front in Gaggenau Silver
Width 60 cm
Controls at the top

Flush installation
Continuous flow heater means no waiting time and constant brewing temperature
Aroma brewing technology for a full aroma
Single portion cleaning
TFT touch display
One-touch operation
Personalisation function
Seven light settings

Type of beverage

Espresso / 2 x Espresso.
Coffee / 2 x Coffee.
White coffee.
Latte macchiato.
Cappuccino.
Milk froth.
Warm milk.
Hot water.

Handling

Rotary knob and TFT touch display operation.
Clear text display in 25 languages.
Personalisation function, up to 8 beverages can be personalised and memorised.
3 beverage size settings; can be individually adjusted to match the size of the cup.
5 coffee strength levels from mild to extra strong.
3 coffee and hot water temperature levels.
4 grinding level settings.
Height-adjustable coffee dispenser up to 15 cm.
Automatic slide-out function.

Features

Grinding unit with ceramic discs.
Separate container for second ground coffee type.
Water pump with 19 bar pressure.
Double grinding and brewing cycles for extra intensity for one beverage.
Double grinding and brewing cycles for two beverages.
Dispenser with integrated milk system.
Insulated milk container for up to 0.55 litres.
Integrated lighting with 3 LEDs.
Bean container for 1 kg.
Automatic adjustment of ground coffee quantity.
Removable 2.5 litre water tank.
Electronic fill level control for coffee beans and water.
Electronic water filter exchange indicator.
Electronic fill level control for drip tray and container for coffee dregs.

Safety

Child lock.
Safety shut-off.

Cleaning

Fully automatic rinse programme when machine is turned on/off.
Automatic quick rinsing of milk system.
Automatic cleaning and descaling programme.
Removable brewing unit.
Coffee dregs container and drip tray dishwasher-safe.
Milk frother dishwasher-safe.

Planning notes

Ideal installation height 95 cm (top edge of niche bottom), max. 120 cm.

Characteristics

Built-in / Free-standing
Frothing nozzle
Yes
Display
Water protection system
no
Portion sizes
All cups
Dimensions of the product (mm)
455 x 590 x 555
Dimensions of the packed product (HxWxD) (mm)
540 x 600 x 670
Required niche size for installation (HxWxD)
450 x 564 x 514
Hot water spout
Yes
Adjustable programs
Standby function
Yes
Pump pressure (bar)
19
Simultaneous preparation of 2 cups
Yes
Included accessories
1 x measuring spoon, 1 x assembly screws, 1 x milk container, 1 x descaling container, 1 x test strip, 1 x connection hose for milk frother
Optional accessories

Consumption and connection features

Electrical connection rating (W)
1700
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50/60
Plug type
Gardy plug w/ earthing
Product group
Built-in coffee machine
Brand
Gaggenau
Product name/family
Product name / Commercial code
CMP250130
Universal Product Code
825225915225
Main colour of product
Alu
Typology
Fully automatic
Approval certificates
CE, ROSTEST, VDE
Length electrical supply cord (cm)
150.0
Length of electrical supply cord (in)
Recommended height for installation (in)
Recommended height for installation (mm)
450
Appliance Dimensions (h x w x d) (in)
Dimensions of the product (mm)
455 x 590 x 555
Dimensions of the packed product (in)
Dimensions of the pallet (in)
Dimensions of the packed product (HxWxD) (mm)
540 x 600 x 670
Net weight (lbs)
60
Net weight (kg)
27.00
Gross weight (lbs)
65
Gross weight (kg)
29.50
Capacity water container
2.5
2017-07-12
Page 1

Necessary lateral gap between appliance front and furniture panel of min. 5 mm.

The door panel surface of the appliance extends 21 mm from the furniture cavity.

When installing in a corner a side clearance of 200 mm is required.

Installation directly above 14 cm high WS in 59 cm standardised niche.

Special accessories (order as spare parts):

Part No. 467873 Water-filter cartridge

Part No. 311138 Descaling agent

Part No. 310575 Cleaning tablets

Connection

Total connected load 1.70 kW.

Connection cable 1.5 m with plug.

