

UM30N



Colour range
Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



Optional RAL – RA

Finishes
Knobs, handles, frames



Brass – G



Copper – P



Chrome – C



Burnished – B

Optional solid door version

optional +


Order code: add letter "Q" before the "N" letter

Available ovens


Electric oven
Primary oven:
UOV 76 E3 TFT S
Maximum input:
3.7 kW

Configurations

5 burners



Induction



Electric oven

UM30DNE3
Brass/Copper/Chrome/Burnished

UMI30NE3
Brass/Copper/Chrome/Burnished

Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 15.4

All electric
Voltage: 240 Volts
Amps: 47.5

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

- 

Bridge induction zone
Ø 7" 1/4 + Ø 7" 1/4
1.85 / 2.5 kW +
1.85 kW
- 

Induction zone
Ø 5" 3/4
1.4 / 1.8 kW
- 

Induction zone
Ø 7" 1/4
1.85 / 2.5 kW
- 

Induction zone
Ø 8" 11/16
2.3 / 3.2 kW
- 

Double ring Dual burner
20000 btu/h /
900 btu/h
- 

Big burner
10500 btu/h /
2000 btu/h
- 

Small burner
7000 btu/h /
1400 btu/h

Complements & accessories

Hood UAM76 Ladle holder panel AM4-76

Technical drawing & dimensions

