

General Specifications

Two channels driven, 4Ω / 8Ω, 20Hz – 20kHz: 380W / 225W

One channel driven, 8Ω bridged mode, 20-20kHz: 790W

Harmonic distortion, 80% power, 8Ω at 1kHz: 0.001%

Input sensitivity 200W / 8Ω: 1.15V RMS (RCA Type), 2.3V RMS (XLR Type)

Signal/Noise ratio (A-wtd) 50W / 8Ω: 110dB

Input impedance: 10kΩ

Frequency response: 20 - 20kHz +/-0.05dB

Mains voltage: 110–120V or 220–240V, 50–60Hz

Maximum power consumption: 1.5kW

Dimensions W x H x D (including feet, control knob and speaker terminals): 433 x 425 x 177mm

Weight (net): 18kg

Weight (gross): 19.7kg

Audio Specifications

**Two channels driven, 4Ω / 8Ω, 20Hz
– 20kHz**

380W / 225W

**One channel driven, 8Ω bridged
mode, 20-20kHz**

790W

**Harmonic distortion, 80% power, 8Ω
at 1kHz**

0.001%

Input sensitivity 200W / 8Ω

1.15V RMS (RCA Type), 2.3V RMS (XLR Type)

Signal/Noise ratio (A-wtd) 50W / 8Ω

110dB

Input impedance

10kΩ

Frequency response

20 - 20kHz +/-0.05dB

Mains voltage

110–120V or 220–240V, 50–60Hz

Maximum power consumption

1.5kW

**Dimensions W x H x D (including
feet, control knob and speaker
terminals)**

433 x 425 x 177mm

Weight (net)

18kg

Weight (gross)

19.7kg