

Product Specifications

Style Number	VV735
Construction	Waterproo
Edge Profile	Pressed B
Nominal Dimensions	7" wide, 6
US Units	
Actual Product Width	7.05"
Actual Product Length	59.84"
Wear Layer Thickness	20 mil (0.0
Overall Product Thickness	0.295"
Core Thickness	0.197"
Attached Underlayment	Attached
Attached Underlayment Thickness	0.039"
Finish	UV Acrylic
Installation Methods	Floating o
Profile	Angle/Tap
Country of Origin	Imported

Packaging

Area per Box	23.43 sq f
Pieces per Box	8 pcs
Weight per Box	36.68 lbs
Boxes per Pallet	65 boxes



3018 Tyro Walnut

Colors



CT HD 7X60 INTG

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- USF Lifetime Limited
- [Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)
- USF 10 Year Medium Commercial


Certifications

GreenGuard (Certification, Gold, Private Label) Certified


Coordinating Trim




Baby Threshold*
BT7CT | 94"



T-Molding*
TM7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS7HU | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"

