


KM 7745 FL
 Induction Cooktop
 with 3 PowerFlex cooking areas for maximum performance




- Communication with the ventilation hood – automatic Con@ctivity function
- Intuitive quick selection via number sequences – Smart Select
- Shortest heating-up times – TwinBooster
- 6 cooking zones incl. 3 high-power PowerFlex cooking areas
- With a width of 35 7/8 (909) in (mm) for proud-mounted or flush-mounted installation

EAN: 4002516611615 / Material number: 12074230 / Old Material Number: 26774570USA

Heating type	
Fuel type	Induction
Design	
Independent of oven	•
Design	
Elegant glass ceramic surface	•
Flush	•
Ceramic surface colour	Black
Proud installation	•
Cooking zone details	
No. of rings	6
Number of cooking areas	3
Maximum number of pans	6
PowerFlex cooking zones	
No.	6
Type	PowerFlex cooking zone
Diameter in inches	Ø 150 – 230
Power in W	2100
Booster in W	3000
TwinBooster in W	3700
1st cooking zone/cooking area	
Position	Left
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	3400
Max. rating in W	3100
Max. TwinBooster power rating in W	3700
2nd cooking zone/cooking area	
Position	Centered
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	4800
Max. rating in W	3400
Max. TwinBooster power rating in W	7400
3rd cooking zone/cooking area	
Position	right
Type	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	4800
Max. rating in W	3400
Max. TwinBooster power rating in W	7400
User convenience	
Miele@home	•
Operation via sensor controls	Smart Select
Automatic function	Con@ctivity 3.0
Pan and pan size recognition	•
Display colour	Yellow
Auto heat-up	•
Keeping warm	•
Stop & Go function	•

KM 7745 FL
 Induction Cooktop
 with 3 PowerFlex cooking areas for maximum performance



EAN: 4002516611615 / Material number: 12074230 / Old Material Number: 26774570USA

Recall function	•
Safety switch-off	•
Permanent pan recognition	•
Individual setting options (e.g. buzzers)	•
Wipe protection	•
Minute minder	•
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety cut-out	•
Lock function	•
System lock	•
Integrated cooling blower	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions (width) in in. (mm)	35 7/8 (909)
Dimensions (height) in in. (mm)	4 1/8 (103)
Dimensions in mm (depth)	21 1/4 (538)
Cutout dimensions (width) in in. (mm)	34 1/2 (876)
Cutout dimensions (depth) in in. (mm)	20 1/2 (518)
Casing height incl. connection box in mm	4 1/8 (103)
Internal cutout dimensions in mm (width) with flush installation	889
Internal cutout dimensions in mm (depth) with flush installation	518
Weight in lbs. (kg)	50 (23)
External cutout dimensions in mm (width) with flush installation	913
External cutout dimensions in mm (depth) with flush installation	542
Total connected load in kW	11.20
Power cord length in in. (m)	3 (1.2)
Voltage in V	208-240
Frequency in Hz	50-60
Standard accessories	
Power cord	Yes