JR-6

STEREO ROCK SPEAKER



SPECIFICATIONS

FREQUENCY RESPONSE	67Hz-22KHz
HIGH FREQUENCY DRIVER	Dual .75" (1.9cm) Aluminum Tweeters
LOW FREQUENCY DRIVER	6.5" (16.5cm) DVC IMG Woofer
SENSITIVITY	88dB (2.83V @ 1m)
POWER HANDLING	2 x 50W
IMEDANCE	2 x 8 Ohm / 70V
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite, Sandstone
GRILLE MATERIAL	Rust-proof Aluminum
DIMENSIONS (H x W x D)	310mm x 307mm x 295mm 12.24" x 12.09" W x 11.65"
WEIGHT	5.53 kg (12.2 lbs)
ACCESSORIES (SOLD SEPARATELY)	JDA-500 DSP Amplifier (120V: 10634321, 230V: 10634322)



DESIGN + PERFORMANCE

The satin painted finish and compact design of the JR-6 allows it to blend seamlessly into even the most luxurious of outdoor living spaces, while the .75" aluminum tweeters and 6.5" dual voice coil IMG woofer provide detailed, dynamic, balanced sound.

SINGLE POINT STEREO

The JR-6 rock speaker is equipped with dual inputs, a dual voice coil woofer, and dual tweeters for true stereo reproduction from a single speaker. Inputs can also be summed to mono for maximum system flexibility in any listening environment, from small residential systems to massive commercial installs.

ALL WEATHER DURABILITY

A UV-resistant, fiberglass cabinet provides the utmost in all-weather capability. With an IP45 rating, the Jamo JR-6 rock satellite is lab tested and certified to offer the best in outdoor audio year in and year out.

OPTIMIZED WITH JDA-500

The new Jamo JDA-500 DSP amplifier is the perfect match for the Jamo rock speakers series - with 70V and low impedence compatibility and one-click Jamo speaker presets to optimize the acoustic performance of your Jamo speakers - no amplifier sounds better with Jamo rock speakers.