

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 + 300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB) A/B
	Frequency Response	20Hz-200Hz (+0dB, -3dB) SUB
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct (SUB)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (SUB)
	Infrasonic Filter	-
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)9-3/4" x (H) 2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 248cm x (H) 53cm x (D) 169cm

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 + 300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB) A/B
	Frequency Response	20Hz-200Hz (+0dB, -3dB) SUB
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct (SUB)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (SUB)
	Infrasonic Filter	-
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)9-3/4" x (H) 2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 248cm x (H) 53cm x (D) 169cm

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 + 300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB) A/B
	Frequency Response	20Hz-200Hz (+0dB, -3dB) SUB
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct (SUB)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (SUB)
	Infrasonic Filter	-
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)9-3/4" x (H) 2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 248cm x (H) 53cm x (D) 169cm

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 + 300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB) A/B
	Frequency Response	20Hz-200Hz (+0dB, -3dB) SUB
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct (SUB)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (SUB)
	Infrasonic Filter	-
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)9-3/4" x (H) 2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 248cm x (H) 53cm x (D) 169cm

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 + 300 Watts RMS x 1 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	1600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	SUB (4 Ohms)	300Watts RMS x 1 (4 Ohms, 20-200Hz, $\leq 0.5\%$ THD)
	SUB (2 Ohms)	500Watts RMS x 1 (2 Ohms, 100Hz, $\leq 0.5\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB) A/B
	Frequency Response	20Hz-200Hz (+0dB, -3dB) SUB
	Input Impedance	10k ohm
	Speaker Impedance	4 Ω (2 Ω to 8 Ω allowable)
	Bridged Connection	4 Ω to 8 Ω allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -24dB/oct (SUB)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (SUB)
	Infrasonic Filter	-
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
	Dimensions(WxHxD)	(W)9-3/4" x (H) 2-1/16" x (D)5-7/8"
	Dimensions(WxHxD)	(W) 248cm x (H) 53cm x (D) 169cm