

1 3077

> BM40AMPBT All Terrain Sound System lease read through these instructions carefully so you will know how to operate your model properly.

After you have finished reading the instructions, keep this document in a safe place for future reference.

# THIS PACKAGE CONTAINS - BM40AMPBT Marine Waketower Speaker System (1 Active + 1 Passive - Bluetooth Multi-Function Controller Handlebar Mounting Kit for Bluetooth Controlle Power Wire Harness Kit

# Bluetooth

- Warranty Card

- User Manual Quick Start Guide / Poste

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks is under license.

Other trademarks and trade names are those of their respective owners.

# 5 J 0 2

## PAIRING & DISCOVERING A NEW BLUETOOTH CONNECTION

1) Power on the **BM40AMPBT** by pressing and holding down the Play/Pause multifunction

button for 3 seconds, the blue LEDs will start to flash, signalling that the BM40AMPBT is now ready for Bluetooth pairing.

NOTE: You have 30 Seconds before you must restart this procedure over again

2) Now that the BM40AMPBT is in pairing mode:

- ANDROID users:
  a. Go into the Settings Menu of your device
  b. Enter the Bluetooth Menu
  c. TURN ON Bluetooth and press SCAN
  d. "BOSS BM40AMPI" will now be displayed under AVAILABLE DEVICES
  e. Press "BOSS BM40AMPIT" to get Bluetooth connected

IOS users:
a. Go into the Settings Menu of your IOS device
b. Enter the Bluetooth Menu
c. TURN ON Bluetooth
d. "BOSS BM40AMPB7" will now be displayed
e. Press "BOSS BM40AMPB7" to get Bluetooth connected

3) If the BOSS BM40AMPBT is not seen, repeat the above steps to refresh the "Device List"

4) When the connection is successful, you are now ready to stream music from your favorite media player to the **BM40AMPBT** 



To avoid potential shorts in the electrical system, be sure to disconnect the (-) bat system, be sure to disconnect the (-) bar-tery cable before installation. Use this unit with a 12-Volt battery and negative ground-ing only. Failure to do so may result in a fire or malfunction.



When replacing the fuse, be sure to only use a fuse of the rating specified on when replacing ne words, the current of the product of the product of the substitution of the product. To avoid short-orculting, cover any disconnected leads with insulating tape; classes easily important to insulate any unused wires, which if left uncovering the any; classes a short circuit. When connecting other devices to this product, refer to the manual the reproduct to be connected. The black ground, make such connected the product of the product of the connected. The black wire is properly accounted to connect the ground wire is properly accounted to the connected that the ground wire is properly accounted to the product of the connected that the ground wire is properly accounted to the product of the product to metal parts of the vehicles body frame or direct to the battery if your vehicle does not have a grounded chassis frame. The ground wire of this unit power amp and a second powered system must be connected to the frame separately with and a second powered system must be connected to the frame separately with different screws. If the screw for the ground wire loosens or falls out, it could result in fire or malfunction.





### FCC COMPLIANCE STATEMENT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions

(1) this device may not cause interference, and

(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of this device.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter. The Bluetooth antenna cannot be removed (or replaced) by antenna or transmitter. The Bluetooth antenna cannot be removed (or replaced) buser. This equipment compiles with FCCV IC radiation exposure limits set forth for an uncontrolled environment and meets the FCC radio frequency (RF) Exposure Guidelines and RSS-102 of the IC radio frequency (RF) Exposure rules. This equipment has very low levels of RF energy that it deemed to comply without maximum permissive exposure (MPE) evaluation. But it is desirable that it should be installed and operated keeping the radiator at least 20 orn ornore away from person's body (excluding extremities: hands, wrists, feet and ankles). Alteration or modifications carried out without appropriate authorization may invalidate the user's right to operate the equipment

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residen tial installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may energy and, it not instance and user in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guar-antee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


Relocate or reorient the receiving antenna.

- Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to which the
- connected.

  Consult the dealer or an experienced radio/TV technician for help.

6

CAUTION!!
ADJUSTMENT OR ALTERATIONS OF THIS DEVICE MAY RESULT IN HAZARDOUS RADIATION EXPOSURE



## RECONNECTION

1) Power on the BM40AMPBT and your last paired device Bluetooth

2) The unit will now automatically reconnect

3) If your device was previously paired with the BM40AMPBT, but it wasn't the last paired


- a. Ensure no other devices are currently paired b. Enter the *Bluetooth Menu* on your device being paired c. "BOSS BM40AMPBT" will display under AVAILABLE DEVICES d. Choose the "BOSS BM40AMPBT" to reconnect

4) If the device is out of range from the BM40AMPBT, it will disconnect automatically

- a. To reconnect once device is back in range, press the Play/Pause
- button once
  b. The BM40AMPBT will now reconnect to the device

To avoid battery exhaustion, be sure to occasionally run the vehicles engine while using this product.

Using this product without running the engine can drain the battery



# B

### IMPORTANT SAFETY PRECAUTIONS

■ Do not operate mobile equipment while driving a motorized vehicle — safe driving and safety consideration of others should always be your highest priority.

In the event you should notice smoke, strange noises or doof from this product, or any other abnormal signs, immediately turn off the power and consult your dealer or the neares authorized BOSS AUDIO Service Center. Using this product in this condition may result in permanent damage to the system.

Set your volume control at all owe setting, then slowly increase the sound until you can set you would not not the system.

BE SURE TO GISSERVE THE FOLLOWING GUIDELINES:

BE SURE TO GISSERVE THE FOLLOWING GUIDELINES:

2. Don oft hum to the volumes so high that you gard these what's around you.

Do not turn up the volume so high that you can't hear what's around you.
 Use caution or temporarily discontinue use in potentially hazardous situations.

### INSTALLATION PRECAUTIONS

### WARNING - Always consult a professional installer

■ Do not attempt to install or service this product by yourself. Installation or servicing of this product by persons without professional training and experience in electronic equipment and motorized vehicle accessories may be dangerous and could expose you to the risk of electric electric inductions.

and motorized whetile accesserions may be dangerous and could expose you to the risk of electric shock, injury or other hazards 

Refer any repairs to a qualified BOSS AUDIO SYSTEMS service Center 

The BMOAMPET can be powered from a vehicles cigarette lighter / auxiliary power port, or hard wired directly to the battlery through an optional relay / accessory switch 

When wring electry to the vehicles battery, be sure to disconnect the startery regative

When winng directly to the vehicles battery, be sure to disconnect the batter negative terminal wire before starting any wifing procedures, it is suggested that an optional flues and fuse holder (not included such minimum rating of 20 Amps be in line with the positive battery terminal the positive battery terminal with the submitted with the submitted with the submitted with the submitted plant in the submitted with the submitted in or under water for any circumstances.
 Use only the installation parts provided with the BM40AMPBT

A CAUTION!! Using other mounting methods may void this warranty

# 6 \* 1))) J 0 (4 **(5)**

## MULTIFUNCTION CONTROLLER BLUETOOTH OPERATION

1) Press the PLAY/PAUSE once to start playing music or press the PLAY button from


2) To skip songs or advance, press the NEXT TRACK button 3) To select the previous song, press the () PREVIOUS TRACK button

## **VOLUME CONTROL**

4) To raise the volume, *Press and Hold* the VOL + button 2 ~ 3 seconds 5) To lower the volume,  $\it Press~ and~ Hold$  the  $\it Old$  vol. - button 2 ~ 3 seconds

Tips: Make sure your device Bluetooth volume is set at 75% level before stowing in to the carry pouch

# 11



# GETTING TO KNOW YOUR BM40AMPBT MULTIFUNCTION CONTROLLER (MFC) 27811

MFC - MULTIFUNCTION CONTROLLER

BLUETOOTH INDICATOR LED(BLUE) / AUX-IN STATUS INDICATOR(RED)

**(5)** 

3.5mm AUX-INPUT

PLAY/PAUSE / Press and hold for POWER ON

PREVIOUS TRACK / Press and hold for VOL -

NEXT TRACK / Press and hold for VOL + /
Warning tone while up to maximum volume
Disconnect any paired Bluetooth device by pressing Clear any paired Bluetooth device in memory by pressing \$\ \frac{1}{8}\$ button for 10 seconds

for 10 seconds

Disconnect any paired Bluetooth device by turning off bluetooth in your device setting menu

in your device setting menu

When power on, blue back lit \(\begin{align\*}{0}\) button sparkles slowly for 30+ seconds to search for ex-paired device; after then \(\beta\) button blue back lit turns to sparkle quickly for similar 30ecs until it is powered off

When Bluetooth devic is out of connection range and Bluetooth pairing is disconnected automatically, and then blue back lit \(\beta\) button sparkles slowly for 1 min to look for ex-paired device, after then \(\beta\) button blue back lit turns to sparkle quickly for simils until it is powered off it is parkled quickly for simils until it is powered off it is powered off.

12 When operation voltage is lower than 9.5Volt, MFC gives warning tone

13 MFC concludes tones of definition : Power On/Off , Bluetooth connection , Disconnection , Maximum volume, Lower voltage

# BM40AMPBT can play audio from any device **(6)** J YOUR DEVICE 0 (5)

# MULTIFUNCTION CONTROLLER AUX-IN OPERATION

1) Power on the BM40AMPBT by pressing and holding down the PLAY/PAUSE multifunction button for 3 second

 Disconnect any paired Bluetooth device by turning off Bluetooth in your devices Settings Menu nect the integrated 3.5mm AUX-IN cable located on right side of the MFC to your

## **VOLUME CONTROL**

4) To raise the volume, *Press and Hold* the VOL + button 2 ~ 3 seconds 5) To lower the volume, **Press and Hold** the  $\bigcirc$  **VOL** - button 2 ~ 3 seconds

Tips: Make sure your device headphone volume is set at 75% level before stowing in to the carry pouch

