## **SCANNO**






Scanno available in 28", 34" & 46" sizes and with only 15 5/8" depth make it perfect to discreetly mount it inside any slim cabinet.

While having a powerful performance of 600 and 1200 CFM blower for extraordinary ventilating power. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED Lighting.





	ESC628SS	ESC134SS	
Α	28½" (87.5 cm)	34½" (87.5 cm)	
В	15 %" (39.8 cm)		
С	5 ½ " (13.8 cm)		
D	6½" (16.4 cm)		
Е	22¾4"(56 cm)	27 % " (70 cm)	
F	12% " (31.6 cm)		
G	24 <sup>21</sup> / <sub>4</sub> "(62 cm)	29 <sup>13</sup> / <sub>16</sub> " (75.7 cm)	
Н	10½"(25.7cm)		
I	10" (25.4 cm)		
J	³¼" (1.9 cm)		

## **ELICA PRO SERIES**

## **SCANNO**





Width:	28" Unit	34" Unit		
Model:	ESC628SS	ESC134SS		
Dimensions:	28 1/2"W x 15 5/8 "D x 11 15/16"H	34 1/2"W x 15 5/8 "D x 11 15/16"H		
Blower Type (Internal):**	600 CFM (4-speed)	1200 CFM (4-speed)		
Nois (sones):**	7.0 Sones	8.5 Sones		
Finish:	Stainless Steel			
Controls:	Fully retractable rotating knobs with white backlighting			
Illumination:	2 LED, 7.5 W 3000 Kelvin, 540 lumens/lamp			
Grease Filter:	Dishwasher-Safe, Professional Stainless Steel Baffle Filters 2 for 28",34" & 3 for 46"			
Duct Transition:	10" Round with BackDraft Damper (top only)			
Installation Type:	Ducted Installation Only			
Electrical:	120V - 60 Hz, 490 W	120V - 60 Hz, 913 W		
KITS:				
1200 CFM External Blower Kit:	KIT0153054			
1200 CFM Inline Blower Kit:	KIT0154387			
10" to 8" transition KIT:	KIT0154387 (1200 CFM)			
Inline Blower Shell Kit:	KIT0179549 (for use with 1200 CFM blowers only)			
External Blower Shell Kit:	KIT0179547 (for use with 1200 CFM blowers only			
Electronic CFM Reduction Bypass Kit:	KIT0185752 (for 600 CFM Blower),KIT0185099 (for 1200 CFM Blower)			
WARRANTY:***	Two (2) Years Parts & In-Home Labor. Earn an additional One (1) Year of Parts & In-Home Labor by registering on elica.com.			

## PLUS FEATURES



HUSH SYSTEM - An exclusive sound deadening technology that effectively reduces sound levels by over 35%



STAINLESS STEEL BAFFLE FILTERS WITH GREASE COLLECTORS - Designed for high airflow cooking, the "S" shape design traps high volumes of grease



SEAMLESS CRAFTSMANSHIP - Heavy gauge stainless steel "Seamless" construction that delivers refined elegance.



PROFESSIONAL PERFORMANCE - Special features and high performances for models with aspiration capacity between 600 and 1200 CFM's



HEAT GUARD - Senses extreme temperatures (>158 degrees) and automatically adjusts the blower speed to HIGH







Model	HVI Certified Ratings	High Speed	Working Speed	Duct Size
ESC134SS	CFM	860	320	10" (Vertical)
	Sones	12.5	2	10" (Vertical)
ESC628SS	CFM	500	180	10" (Vertical)
	Sones	9.5	2	10" (Vertical)

 $<sup>^{\</sup>ast}$  The product images shown are for illustration purposes only and may not be an exact representation of the product.

<sup>\*\*</sup> Blower performance indicates the performance of the blower by itself. Performance claims are not HVI certified but were established in accordance with HVI Standardized test procedure. For Certified Ratings, please refer to HVI Certified Product Directory. Electric Ratings are declared according to UL.

<sup>\*\*\*</sup> For valid warranty extension, register within 3 months from purchase. For USA & Canada Users Only.