# Technical Specifications

C5-Series Power Amplifier – C53/C54/C55

| | |
|---|---|
| Power output | 3/4/5*150W in 8 Ohms (C53/C54/C55) |
| Mains current | 7A at 230V, 14A at 115V (5*150W output) |
| Minimum load | 2 ohms |
| Analog Inputs | 3/4/5*balanced (XLR), 3/4/5*unbalanced (RCA), |
| Control Inputs | 1*mini-jack 5-12V trigger |
| Control Outputs | 1*mini-jack 12V trigger out |
| Gain control | Switchable between 23dB or 29dB (individual) |
| Phase control | Switchable 0°/180° (individual) |
| Frequency response | 5Hz-100kHz |
| Signal-to-noise ratio | More than 100dB |
| Crosstalk | Less than -100dB |
| Distortion | Less than 0.01% @100W 8 Ohms 1kHz |
| Intermodulation | Less than 0.01% (19kHz + 20kHz) |
| Damping factor | More than 2000 (main power output stage) |
| | |
| Net Weight | 28,5kg/33kg/37,5 Kg |
| Gross Weight | 34kg/38,5kg/43kg |
| | |
| Net Weight US | 61lbs/73lbs/82lbs |
| Gross Weight US | 75lbs/85lbs/95lbs |
| | |
| Dimensions | W*H*D incl handles, ex feet: 48,2cm*13,2cm*52cm |
| Dimensions US | W*H*D incl handles, ex feet: 18.97in*5.2in*20.47in |

## What's in the box:

- User manual
- Power cable
- Feet with screws
- Rear rack brackets