# JTS3000DN/EN/SN GE® 30" Built-In Single Electric Wall Oven

## **DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)**

**NOTE:** Single wall ovens are NOT approved for stacking above or below another single wall oven.

**NOTE:** Wall coverings, countertops and cabinets surrounding the wall oven must be able to withstand a temperature of up to 200°F (94°C).

**NOTE:** If the cabinet in which the wall oven is installed does not have a solid bottom, two braces or runners must be installed to support the weight of the oven. The runners and braces must support up to 220 lbs (99 kg).

**NOTE:** Door handle protrudes 3" from door face. Cabinets and drawers on adjacent  $45^{\circ}$ and  $90^{\circ}$  walls should be placed to avoid interference with the handle.

**ATTENTION INSTALLER:** Electric wall ovens are NOT approved for installation with a plug and receptacle. They must be hard wired into an approved junction box.

**IMPORTANT:** Before installing, consult installation instructions packed with product for current dimensional data.

KW RATING		
240V	3.6	
208V	2.7	
BREAKER SIZE		
240V	20 Amps	
208V	20 Amps	







door opening allowance



Dimension and installation information are shown in inches.

Cabinet	30"
A - Overlap of oven at top of cutout	1"
B - Overlap of oven other side of edge of cutout	3/4"
C - Overlap of oven at bottom of cutout	1-1/4"
Oven	
D - Install depth	23-1/2"
E - Overall height with trim	28-5/8"
F - Overall width	29-3/4"



For answers to your GE Profile<sup>™</sup> Series or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center<sup>®</sup> Service, 800.626.2000.

**JTS3000** 

## JTS3000DN/EN/SN GE<sup>®</sup> 30" Built-In Single Electric Wall Oven

## DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**NOTE:** 30" Single electric wall ovens are approved for installation below a countertop, and below certain gas and electric cooktops. Refer to the Approved Combinations Matrix available at geappliances.com for specific information.

**NOTE:** 30" Single electric wall ovens are approved for installation above 27" and 30" warming drawers.

**ATTENTION INSTALLER:** Electric wall ovens are NOT approved for installation with a plug and receptacle. They must be hard wired into an approved junction box.

**IMPORTANT:** Before installing, consult installation instructions packed with ALL products for current dimensional and combination data.



NOTE: One cooktop may be centered over either

GE APPLIANCES

# oven in the side-by-side installation.

For answers to your GE Profile<sup>™</sup> Series or GE Appliances product questions, visit our website at geappliances.com or call GE Answer Center® Service, 800.626.2000.

#### Gas or Electric Cooktops May Be Installed Over This Oven. 240V/208V See Cooktop Installation Instructions for Cutout Size. Junction Box See Label on Top of Oven for Approved Models. Location (junction box may be in adjacent cabinet) Gas or Electric Connections for Gas 25" (63.5 cm) Cooktop Must be Located in an Adjacent Accessible Location to the Right (Ú.) Top and/or Side Fillers 135 135 May Be Necessary if Unit is Positioned Between Existing Cabinets. Be Sure They Are Attached Securely, Since They Will Anchor the Oven 22" (55.9 cm) min. 36" (91.4 cm) Above Support Countertop in the Cabinet. Platform Height 3/4" (1.9 cm) Must Match Support Platform Toekick Height Required

UNDERCOUNTER INSTALLATION

## INSTALLATION BELOW A COOKTOP

IMPORTANT: Maintain a minimum distance of **31 1/4**" from the top surface of the countertop to the wall oven platform to ensure that the cooktop and wall oven do not interfere with each other (see picture).

MUST SUPPORT 220 lbs. (99 kg) FOR SINGLE OVENS



24" (61 cm)

4" (10.2 cm) Toekick

# JTS3000DN/EN/SN GE® 30" Built-In Single Electric Wall Oven

## FEATURES AND BENEFITS

Never scrub, heavy-duty racks – Say goodbye to scrubbing thanks to never scrub heavy-duty racks, engineered to withstand a self clean cycle

Self-Clean with optional Steam Clean – Cleaning the oven interior has never been easier, with two cleaning options to fit your lifestyle

Anywhere control with remote notifications – Save time by conveniently preheating and monitoring your oven from anywhere using the GE Appliances Kitchen app

Scan-to-cook – Prepare your favorite packaged foods to perfection simply by scanning the barcode on the package with your smartphone and letting your oven adjust settings automatically

Glass touch controls - Set temperatures quickly and clean with little effort

10-pass hidden bake element – Even baking and quick cleanup are assured, with 10-pass element that heats a large cooking area and is hidden for an easy-to-wipe surface

8-pass broil element - Get full broil coverage and even browning from edge to edge

Model JTS3000DNBB – Black Model JTS3000DNWW – White Model JTS3000SNSS – Stainless steel Model JTS3000ENES – Slate

### **FIT GUARANTEE**

Replacing a similar wall oven from GE Appliances or another brand? GE wall ovens are guaranteed for an exact fit or GE Appliances will pay up to \$300 toward modifications.

Visit geappliances.com for more info



