

FM	(Frequency step)	(200kHz)
	Usable sensitivity	16.2dBf
	S/N:30dB	1.8μV/75 Ohms
	Quieting sensitivity	-
	DIN S/N 46dB	13dBf(4.47uV/75 ohm)
	Frequency response (±3.0dB)	30Hz - 14kHz
	S/N (dB)	50dB (MONO)
	Selectivity	Over 80dB
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99μV(40dBμ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power (at less than 1%THD)	21Wx4
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)

FM	(Frequency step)	(200kHz)
	Usable sensitivity	16.2dBf
	S/N:30dB	1.8μV/75 Ohms
	Quieting sensitivity	-
	DIN S/N 46dB	13dBf(4.47uV/75 ohm)
	Frequency response (±3.0dB)	30Hz - 14kHz
	S/N (dB)	50dB (MONO)
	Selectivity	Over 80dB
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99μV(40dBμ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power (at less than 1%THD)	21Wx4
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)

FM	(Frequency step)	(200kHz)
	Usable sensitivity	16.2dBf
	S/N:30dB	1.8μV/75 Ohms
	Quieting sensitivity	-
	DIN S/N 46dB	13dBf(4.47uV/75 ohm)
	Frequency response (±3.0dB)	30Hz - 14kHz
	S/N (dB)	50dB (MONO)
	Selectivity	Over 80dB
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99μV(40dBμ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power (at less than 1%THD)	21Wx4
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)

FM	(Frequency step)	(200kHz)
	Usable sensitivity	16.2dBf
	S/N:30dB	1.8μV/75 Ohms
	Quieting sensitivity	-
	DIN S/N 46dB	13dBf(4.47uV/75 ohm)
	Frequency response (±3.0dB)	30Hz - 14kHz
	S/N (dB)	50dB (MONO)
	Selectivity	Over 80dB
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99μV(40dBμ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power (at less than 1%THD)	21Wx4
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)

C a >	FM	(Frequency step)	(200kHz)
		Usable sensitivity	16.2dBf
		S/N:30dB	1.8μV/75 Ohms
		Quieting sensitivity	-
		DIN S/N 46dB	13dBf(4.47uV/75 ohm)
		Frequency response (±3.0dB)	30Hz - 14kHz
		S/N (dB)	50dB (MONO)
		Selectivity	Over 80dB
		Stereo separation	35dB (1kHz)
AM		Frequency Range	530 - 1700 kHz
		(Frequency step)	(10kHz)
		Usable sensitivity	99μV(40dBμ)
Video		Color system of external video input	NTSC/ PAL
		External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
		External audio max input level (RCA jacks)	1.5V / 25k Ohms
		Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio		Maximum Power Output (Front&Rear)	45Wx4
		Full Bandwidth Power (at less than 1%THD)	21Wx4
		Output frequency band	20 - 20,000Hz
		Preout level (V)	2.0V / 10k Ohms
		Preout impedance (Ω)	1.4k Ohms
		Speaker Impedance (Ω)	4-8 Ohms
A KI		Operating voltage	12V DC Car Battery
		Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)

FM	(Frequency step)	(200kHz)
	Usable sensitivity	16.2dBf
	S/N:30dB	1.8μV/75 Ohms
	Quieting sensitivity	-
	DIN S/N 46dB	13dBf(4.47uV/75 ohm)
	Frequency response (±3.0dB)	30Hz - 14kHz
	S/N (dB)	50dB (MONO)
	Selectivity	Over 80dB
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99μV(40dBμ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power (at less than 1%THD)	21Wx4
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 153 (mm) 7-3/16 x 4-7/16 x 6 (inch)