

UM09N



Colour range
Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



RAL
Optional RAL – RA



Brass – G



Copper – P



Chrome – C



Burnished – B

Finishes
Knobs, handles, frames

Optional solid door version
optional +

Order code: add letter "Q" before the "N" letter

Available ovens


Electric oven

Primary oven:
UOV 80 E3 TFT S


Maximum input:
3.7 kW

Configurations

6 burners with fry top*



Induction



Electric oven

UM09FDNS3
Brass/Copper/Chrome/Burnished

UMI09NS3
Brass/Copper/Chrome/Burnished

Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 18.1

All electric
Voltage: 240 Volts
Amps: 66

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

Bridge induction zone
Ø 7" 1/4 + Ø 7" 1/4
1.85 / 2.5 kW + 1.85 kW

Induction zone
Ø 5" 3/4
1.4 / 1.8 kW

Induction zone
Ø 7" 1/4
1.85 / 2.5 kW

Induction zone
Ø 8" 11/16
2.3 / 3.2 kW

Induction zone
Ø 10" 1/4
2.6 / 3.7 kW

Double ring Dual burner
20000 btu/h / 900 btu/h

Griddle
10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h

Big burner
10500 btu/h / 2000 btu/h

Small burner
7000 btu/h / 1400 btu/h

Complements & accessories

Hood UAM90 Ladle holder panel AM4-90

Technical drawing & dimensions

