

Product data sheet

CONSTRUCTION TYPE

Fully integrated dishwashers	•
60 cm dishwashers	•

DESIGN

Control panel colour	Stainless Steel.
Control panel version	Fully integrated fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow

CONVENIENCE

Door closing aid	ComfortClose
Time left display	•
Delay start up to 24 h	•
In-operation indicator light	acoustic
Operating noise dB(A) re 1 pW	42

EFFICIENCY AND SUSTAINABILITY

Hot-water connection	•
Proven hygiene	•
ENERGY STAR® Most Efficient	•

EcoPower technology

•

QUALITY OF RESULTS

Fresh-water dishwasher

•

AutoOpen drying

•

SensorDry

•

Recirculation turbothermic drying

•

Perfect GlassCare

•

WASH PROGRAMS

Automatic

•

Intensive 75°C

•

QuickIntenseWash

•

Sanitize

•

Rinse & Hold

•

CLEANING OPTIONS

Short

•

Extra clean

•

Extra dry

•

TECHNICAL DATA

Minimum niche height in mm

33 3/4 (855)

Appliance width in mm

23 5/8 (598)

Appliance height in mm

33 3/4 (855)

Appliance depth in mm

22 1/2 (570)

Appliance depth with door open in cm	47 1/2 (120.5)
Net weight in kg	100 (45.0)
Total rated load in kW	1.400
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in cm	5 (1.50)
Length of water drain hose in cm	5 (1.50)
Length of power cable in m	4 (1.20)
Minimum niche width in mm	23 5/8 (600)
Niche depth in mm	21 3/4 (550)
Maximum niche width in mm	23 5/8 (600)
Maximum niche height in mm	36 1/4 (920)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[retro-fittable by Service to min.]	7.0
[retro-fittable by Service to max.]	14.0

BASKET DESIGN

Cutlery loading	3D MultiFlex tray
Basket design	Comfort
FlexCare cup rack	1

SAFETY

Waterproof system	•
--------------------------	---