

System Format

Active

Frequency Response (In-room, -6dB)

17 — 200 Hz

Maximum Usable SPL - Peak (CTA 2010-B, Z-weighted, half-space)

117 dB

Amplifier Output Instantaneous (RMS)

500 W

Amplifier Classification

High-Efficiency Class-D

Bass Alignment

Ported

Low Pass Filter Frequency (-6dB)

32 — 200 Hz

Inputs

Stereo Unbalanced RCA
LFE Unbalanced RCA
12 V Trigger 3.5 mm mono jack

Input Impedance

47 kOhms

Phase Control

0° & 180° Toggle Switch

Equalisation DSP

3 pre-set modes: Impact, Movie, Music

Auto Music Sensing

Auto On: Line Level >3 mV | Auto Standby after 20 mins

Mains Input Voltage

Universal Mains, 85 - 265 VAC, 50 - 60 Hz

Power Consumption (1/8th Maximum Output)

120 W

Drive Unit Complement

1x 15" (381 mm) High Linear-Excursion Triple Suspension Driver

External Dimensions with all accessories fitted (H x W x D)

540 x 526 x 556 mm (21^{1/4} x 20^{11/16} x 21^{7/8} ")

Weight

30.3 kg

Grille

Cloth covered

Warranty

5 years