

Thank you for purchasing Leick Furniture products. Contact customer service for comments or concerns.

Sheboygan, WI

800-558-8700

cs@todaysdesignhouse.com

todaysdesignhouse.com

Note:

A packet with complete set of hardware can be found by pulling the red ribbon that's easily visible upon opening the box.


Assembly Instructions, #70010 Fletcher Desk



| A: Shelf | | 1 |
|---------------------|---|----|
| B: Back Panel | | 1 |
| C: Desk top | | 1 |
| D: Left Side Frame | | 1 |
| E: Right Side Frame | | 1 |
| F: Back Side Frame | | 1 |
| G: Long Bolts | © \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | 3 |
| H: Short Bolts | 6) ////////// | 10 |
| I: Lock Washers | G | 13 |
| J: Flat Washers | | 13 |
| K: Allen Wrench | | 1 |
| L: Wooden Dowels | OTTO TO | 3 |
| | | |


Step 1

- **1.1** Insert right side frame's (E) metal tube onto back frame (F), fasten with 2 short bolts, lock washers and flat washers.
- **1.2** Place the top (C) side up as per following sketch, insert the top metal tube onto right side frame, fasten with 1 short bolt, lock washer and flat washer. Tighten.




Step 3

Insert the left side frame onto tubes of top and back frame. Fasten with three short bolts, lock washers and flat washers. Tighten.




Step 2

Place the back panel (B) with wire cover facing up onto desk top, fasten with 3 long bolts, lock washers and flat washers.



Step 4

Insert three wooden dowels into predrilled holes of back panel. Align shelf's (A) holes with wooden dowels and fasten with 4 short bolts through side frames' tabs into the bottom of shelf.



Step 5

Place the writing desk upright. Adjust the levelers on the bottom of side frames if needed.

Wire management hole on back of desk: pull the disk out, run wires, and snap disk back in place.



