

SPECIFICATIONS

INPUTS

Inputs: 8 Balanced Inputs, 8 Unbalanced RCA Inputs, 2 Digital Combo Coax/Toslink Inputs

Input Sensitivity: 1 Vrms for full output, level at maximum

Input Gain: 30 dB

OUTPUTS

Amplifier Channels: 4

Power Output (70 V / 100 V): 750W per channel

Power Output (70 V / 100 V Bridged Mono): 1500W

Power Output (8Ω): 500W per channel

Power Output (2Ω / 4Ω): 750W per channel

Power Output (4Ω / 8Ω Bridged Mono): 1500W

Minimum Speaker Load: 2Ω

Preamp Audio Outputs: 4 Balanced, 4 Unbalanced RCA, 4 Digital Coax Loop Outputs

CONTROL

Remote Power Trigger: +12 VDC or Dry Contact Closure

Network Connection/Protocol: 10BaseT Ethernet TCP/IP

Communication Protocol: HTTP or Telnet

WEIGHTS & DIMENSIONS

Dimensions: 17" W x 15.5" D x 3.5" H (2U)

Weight: 18.5 lbs (8.4 kg)

IN THE BOX: Model CM4-750, Speaker Connectors, Remote Connector, Power Cord, Manual, Warranty